

# CP-UD-0209L-4K

## Ultra-HD Network Video Decoder

- Instastream/H.265/H.264/MJPEG/MPEG4/MPEG2 video decoding
- Ultra-high decoding ability, up to 12MP
- 2ch HDMI and 2ch DVI-I input, 9ch HDMI output
- Support 1/4/9/16 display split
- Support audio, alarm, bi-directional talk, RS485
- Splicing screens control for zoom/merge/roam/overlay



### About CP PLUS

The brand that is on its way to lead the world when it comes to the security and surveillance industry, CP PLUS, keeps bombarding the market with the most reliable range of products that have been designed carefully and methodically to automate the whole surveillance and security process, no matter how big your premises are.

It was the initiative to help the public in the area where they are the most vulnerable and to empower the sense of safety in our hearts that had conceptualized CP PLUS. And embarking on its mission to make the world a safer and more secure place has taken the brand's journey to unprecedented levels even when compared to international competitors.



# CP-UD-0209L-4K

## Ultra-HD Network Video Decoder

Feature	Specification
Processor	Embedded processor
Operating System	LINUX
Video Format	MPEG2/MPEG4/H.264/H.265/Instastream/MJPEG
Audio Format	PCM/G711/AAC
Decoding Capacity Separately	Port 1,2,3- 3CH@12MP/4CH@4K/16CH@1080P/36CH@720P/48CH@D1 Port 4,5,6 - 3CH@12MP/4CH@4K/16CH@1080P/36CH@720P/48CH@D1 Port 7,8,9 - 3CH@12MP/4CH@4K/16CH@1080P/36CH@720P/48CH@D1
Total Video Decoding	9CH@12MP/12CH@4K/48CH@1080P/108CH@720P/144CH@D1
Decoding Resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080P/720P/960H/D1/HD1/2CIF/CIF/QCIF
Video Output	9ch HDMI
Display Resolution	3840×2160/2560×1600/1920×1080/1280×1024/1280×720/1024×768, only 6 ports support 3840×2160, the remaining 3 ports support 2560×1600
Audio Output	9ch HDMI
Communication Interface	2 RJ45 network port (10M/100M/1000M); 3 RS232(1 DB9, 2 RJ45); 1 RS485
Bi-directional Talk	1 Pair 3.5mm jack (2.0V Line in/50mV Mic in/10KΩ, 2.0V/16Ω out)
Alarm Input	4ch
Alarm Output	4ch relay out (30VDC 1A, 125VAC, 0.5A)
Power Supply	AC100-240V, 50Hz-60Hz
Power Consumption	≤70W
Working Temperature	-10 °C to +55 °C (14 °F to 131 °F)
Working Humidity	10~90%RH / 86~106kpa
Dimension	440×408×70mm(17.32 × 16.06 × 2.76 inch), (W x D x H)
Weight	4.83kg

Dimension (mm/inch)

