

CP-URP-H75FC1-4K

75" 4K Ultra HD Interactive Display

- Android and Windows can be easily switched between (PC module is required for Windows OS)
- 4K Ultra HD display that delivers a clear and sharp image, Vivid Color feature Supported
- Screen sharing from multiple devices through wirelessly, such as Smart Phones, Computers, and Tablet
- Touch Screen Panel
- Built in Camera (5MP), Built In Mic, Built-in office document and media files support
- Supports Dual Band Wi-Fi, Hot-Spot with enabling Hotspot and Wi-Fi at the same time Feature



About CP PLUS

The brand that is on its way to lead the world when it comes to the security and surveillance industry, CP PLUS, keeps bombarding the market with the most reliable range of products that have been designed carefully and methodically to automate the whole surveillance and security process, no matter how big your premises are.

It was the initiative to help the public in the area where they are the most vulnerable and to empower the sense of safety in our hearts that had conceptualized CP PLUS. And embarking on its mission to make the world a safer and more secure place has taken the brand's journey to unprecedented levels even when compared to international competitors.



CP-URP-H75FC1-4K

75" 4K Ultra HD Interactive Display

Feature	Specification
Display Size	75 inch (190.5 Cm.)
CPU	Quad-core A55
Operating System	Android 9
O.S. of External Module	Windows 7/8/10; Android
RAM & ROM	4 GB & 32 GB
Aspect Ratio	16:9
Contrast Ratio	Static Contrast: 1200:1 Dynamic Contrast: 6000:1
Backlight	DLED
Brightness	350 cd/m ²
Resolution	Panel resolution: 3840 (H) × 2160 (V) Camera Resolution: Android: 1920 × 1080@30 fps OPS: 2560 × 1440@30 fps
Viewing Angle	178°(H)/178°(V)
Refresh Rate	60 Hz
Pixel	Camera Pixel: 5MP
Lifespan	50,000 hours
Field of View	H: 79°; V: 51°; D: 88°
Wi-Fi	Dual-band Wi-Fi (2.4/5 GHz)
Wi-Fi Hotspot	Dual-band (2.4/5 GHz); supports enabling Hotspot and Wi-Fi at the same time
Touch Technology Type	Infrared Touch Technology
Light Sensor	1 (one)
Touch Response Time	<10 ms
Touch Points	20
Valid Touch	2 mm
Touch Resolution	32767 × 32767
Writing Mode	Finger + Pen
Auto Control	Auto white balance

Feature	Specification
IrDA	1
Distortion	≤5%
Front Button	1 × power button (right side)
Ports	1 × RJ-45, 1 × Wi-Fi; 1 × Hotspot, 1 × RS-232, 1 × HDMI IN, 1 × 3.5 mm (Line OUT) port, 3 × USB 3.0; 1 × Micro USB
Number of Multi-user Writing Points	2 (Two)
Number of Microphones	2 (Two)
Microphone Pick-up Distance	Far-field sound pickup: 6 m–8 m (19.69 ft–26.25 ft)
Built-in Speaker	2 (Two)
Speaker Power	Full frequency: 15 W × 2
AGC	Supported
Noise Cancellation	Supported
Polar Pattern	Omnidirectional
Echo Cancellation	Supported
Display Glass	Anti-dazzle tempered glass with a hardness of 7 on the Mohs scale
Glass Thickness	3mm
Power Supply	100–240 VAC, 50/60 Hz
Power Consumption	300 W
Standby Power Consumption	0.5 W
Operating Temperature	-10 °C to +45 °C (+14 °F to +113 °F)
Storage Temperature	-20 °C to +55 °C (-4 °F to +131 °F)
Humidity	Operating Humidity: 10%–90%; Storage Humidity: 10%–90%
Frame Color (Front/Back)	Bottom: Silver; top/left/right: black
Dimensions	Panel Dimensions: 75-inch, Product Dimensions: (with camera): 1,707 mm × 87 mm × 1,066 mm (67.2" × 3.43" × 41.97")
Casing	Metal
Weight	54 kg (119.1 lb)

Company Name:

CP PLUS (Aditya Infotech Ltd.)

F-28 Okhla Industrial Area, Phase 1,

New Delhi 110020, INDIA

Contact Mail ID :- customercare@cpplusworld.com

