

**CP- UVC-RC4K08L2-VD****Multi-Lens Panoramic HDCVI IR Camera - 20 Mtr.****Main Features**

- Three 1/2.8" 2MP Progressive scan CMOS Image Sensor
- Max. 15fps@4K, 25fps@4MP
- 1 panoramic view and 3 individual 2MP video output simultaneously
- WDR(120dB), Day/Night (ICR), 2D/3D-DNR, AWB, AGC, BLC, HLC
- 3.6mm fixed lens
- IR Range of 20 Mtrs, IP67, IK10
- Up to 500m transmission with RG59 coaxial cable



**CP- UVC-RC4K08L2-VD****Multi-Lens Panoramic HDCVI IR Camera - 20 Mtr.****Feature**

Image Sensor  
Effective Pixels  
Minimum Illumination  
Shutter Speed  
White Balance  
Gain Control (AGC)  
Lens  
S/N Ratio  
Angle of View  
Back Light Compensation  
Video Streaming  
Video Output  
Resolution  
ICR  
Audio Input  
Test Interface  
Menu set  
Alarm IN  
Alarm Out  
IR  
Operating Temperature  
Power Source  
Power Consumption  
Weatherproof Standard  
Dimension  
Weight

**Specification**

Three 1/2.8" 2MP progressive scan CMOS  
Panorama: 4K(3840x832)/4MP(2560x554)  
0.005Lux/F1.8( Color), 30IRE,0Lux/F1.8(IR on)  
PAL:1/4s~1/100,000s, NTSC:1/3s~1/100,000s  
Auto / Manual  
Auto/Manual  
3.6mm lens  
More than 65dB  
H: 180°  
BLC / HLC / WDR(120dB)  
PAL: 3840x2160@12.5fps, 2560x1440@25fps; NTSC: 3840x2160@15fps, 2560x1440@25fps  
1-channel BNC HDCVI panoramic video output & 3-channels BNC 2MP HDCVI video output  
4K (3840X2160)/4MP(2560x1440)  
Auto (Electronic) / Manual  
1-channel audio in (JACK)  
1-channel 2-pin CVBS video output  
1 Five-direction button  
2 Ch.  
1 Ch.  
IR Range of 20 Mtr.  
-30°C~+60°C, Less than 90% RH  
12V DC ±25%  
22W  
IP67 & IK10  
286mm x 119mm x 106mm  
2.05kg