

CP- VNC-T21ZR5-VMDS**2 MP WDR Array Bullet Camera - 50Mtr.****Main Features**

- 1/2.8" 2MP PS CMOS Image Sensor
- Max 25/30fps@1080P
- Ultra 265, H.265, H.264, MJPEG Triple-stream encoding
- Support Super starlight Function
- WDR(120dB), Day/Night (ICR), 2D/3D-DNR, Corridor Mode, ROI, Digital, Defog, AWB, AGC, BLC, HLC
- 2.7~13.5mm Motorized Lens
- Array Range of 50 Mtrs, Smart IR, Micro SD Card, IP67, PoE
- Supports Instastream technology, save disk space and bandwidth upto 70%
- Mobile Software: Android, iOS
- CMS Software: IVMS

**InstaStream**

CP- VNC-T21ZR5-VMDS

2 MP WDR Array Bullet Camera - 50Mtr.

Feature

Image Sensor
 Minimum Illumination
 Shutter Speed
 White Balance
 Lens
 DORI Distance
 Angle of view
 Gain Control (AGC)
 Video Compression
 S/N Ratio
 Back Light Compensation
 Video Streaming
 Resolution
 Frame Rate
 Motion detection
 Privacy Mask
 ICR
 ROI
 Audio Input
 Audio Output
 Audio Compression
 Audio
 Alarm IN
 Alarm Out
 Protocol
 Network Storage
 Ethernet
 IR

Specification

1/2.8" 2MP Progressive scan CMOS
 Colour: 0.0005 Lux (F1.2, AGC ON) 0 Lux with IR on
 Auto/Manual, shutter time: 1~1/100000 s
 Auto/Manual
 2.7~13.5mm Motorized Lens
 2.7mm- 41.9 Detect (m) , 16.8 Observe (m), 8.4 Recognize (m), 4.2 Identify (m)
 13.5mm- 309.5 Detect (m) , 83.8 Observe (m), 41.9 Recognize (m), 20.9 Identify (m)
 121.36° ~ 33.51° (H), 60.2° ~ 13.2° (V), 157.8° ~ 41.2° (O)
 Auto/Manual
 Ultra 265, H.265, H.264, MJPEG
 >52dB
 BLC / HLC / WDR(120dB)
 Triple
 2MP (1920 × 1080)
 Main Stream: 2MP (1920×1080):Max. 30 fps; Sub Stream: 2MP (1920×1080):Max. 30fps; Third Stream: D1(720×576):Max. 30fps
 Up to 4 areas
 Up to 8 areas
 IR-cut filter with auto switch (ICR)
 Up to 8 areas
 impedance 35 kΩ; amplitude 2 V [p-p]
 impedance 600 Ω; amplitude 2 V [p-p]
 G.711
 Two-way audio Supported
 1 IN
 1 Out
 IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, ONVIF (Profile S, Profile G, Profile T), API
 ANR, NAS(NFS)
 1 RJ45 10M/100M Base-TX Ethernet
 Array Range of 50 Mtr. , Smart IR

CP- VNC-T21ZR5-VMDS**2 MP WDR Array Bullet Camera - 50Mtr.****Feature**

OSD

Micro SD

Casing

Operating Temperature

Humidity

Power Source

Power Consumption

Weatherproof Standard

Dimension

Weight

Specification

Up to 8 OSDs

Micro SD, up to 256GB

Metal

-35°C ~ +60°C (-31°F ~ 140°F)

<90% RH (non-condensing)

12 V DC±25%, PoE (IEEE802.3 af)

Max 10W

IP67

253.4 × 86 × 71.7mm (9.98" × 3.4" × 2.8")

1.0 kg