

**CP- VNC-T51ZR5-VMD****5 MP Full HD WDR Array Bullet Camera - 50Mtr.****Main Features**

- 1/2.7" 5MP PS CMOS Image Sensor
- 5MP(2592 x 1944): Max. 25 fps
- Ultra 265,H.265, H.264, MJPEG Triple-stream Encoding
- WDR(120dB), Day/Night (ICR), 2D/3D-DNR, Corridor mode, ROI, Digital defog, AWB, AGC, BLC, HLC
- 2.7~13.5mm Motorized lens
- Array Range of 50 Mtrs, Smart IR, IP67, SD Card, PoE
- Support Instastream technology, save disk space and bandwidth upto 70%
- Mobile Software: Android, iOS
- CMS Software: IVMS

**InstaStream**

# CP- VNC-T51ZR5-VMD

## 5 MP Full HD WDR Array Bullet Camera - 50Mtr.

### Feature

Image Sensor  
 Minimum Illumination  
 Shutter Speed  
 White Balance  
 Lens  
 DORI Distance  
 Gain Control (AGC)  
 Angle of View  
 Back Light Compensation  
 Video Compression  
 S/N Ratio  
 Video Streaming  
 Resolution  
 Frame Rate  
 Motion detection  
 Privacy Mask  
 ICR  
 ROI  
 Audio Input  
 Audio Output  
 Audio Compression  
 Audio  
 Alarm IN  
 Alarm Out  
 Protocol  
 Dewarping

### Specification

1/2.7" 5MP Progressive scan CMOS  
 Colour: 0.002Lux (F1.2, AGC ON) 0Lux with IR on  
 Auto/Manual, shutter time: 1~1/100000 s  
 Auto/Manual  
 2.7~13.5mm Motorized Lens  
 2.7mm– 60.8 Detect (m) , 24.3 Observe (m), 12.2 Recognize (m), 6.1 Identify (m)  
 13.5mm– 303.8 Detect (m) , 121.5 Observe (m), 60.8 Recognize (m), 30.4 Identify (m)  
 Auto/Manual  
 93.38° ~ 28.56°(H), 88° ~ 16.4°(V), 121.4° ~ 33.7°(O)  
 BLC / HLC / WDR(120dB)  
 Ultra 265,H.265, H.264, MJPEG  
 >52 dB  
 Triple  
 2592 x 1944  
 Main Stream: 5MP (2592x1944), Max 20fps; 5MP (2592x1944), Max 25fps (WDR OFF); 4MP (2560x1440), Max 30fps; 3MP (2048x1536), Max 30fps; 2MP (1920x1080), Max 30fps;  
 Sub Stream: 2MP (1920x1080), Max 30fps; Third Stream: D1 (720x765), Max 30fps  
 Up to 4 areas  
 Up to 8 areas  
 IR-cut filter with auto switch (ICR)  
 Up to 8 areas  
 Input: impedance 35 kΩ; amplitude 2 V [p-p]  
 Output: impedance 600 Ω; amplitude 2 V [p-p]  
 G.711  
 Two way Supported  
 1 Ch.  
 1 Ch.  
 IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, ONVIF (Profile S, Profile G, Profile T), API  
 Support

# CP- VNC-T51ZR5-VMD

5 MP Full HD WDR Array Bullet Camera - 50Mtr.

## Feature

Ethernet  
OSD  
IR  
Network Storage  
Smart Phone  
Micro SD  
Casing  
Operating Temperature  
Humidity  
Power Source  
Power Consumption  
Weatherproof Standard  
Dimension  
Weight

## Specification

10M/100M Base-TX Ethernet  
Up to 8 OSDs  
Array Range of 50 Mtr., Smart IR  
ANR (Automatic Network Replenishment), NAS(NFS)  
Android, ios  
Micro SD, up to 256GB  
Metal  
-35°C ~ 60°C (-31°F ~ 140°F)  
≤95% RH (non-condensing)  
12 V DC±25%, PoE (IEEE802.3 af)  
Max.10 W  
IP67  
253.4mm x 86mm x 71.7mm (9.98" × 3.4" × 2.8")  
1.0kg