

**CP- VNC-T41R3M-D****4 MP WDR IR Array Bullet Camera - 30Mtr.****Main Features**

- 1/3" 4MP PS CMOS Image Sensor
- Max 20fps@4MP
- Ultra H.265/H.265/H.264/MJPEG Triple-stream Encoding
- WDR(120dB), Day/Night (ICR), 2D/3D-DNR, Digital Defog, Corridor Mode, ROI, AWB, AGC, BLC, HLC
- 3.6mm lens (6.0mm Optional)
- IR Range of 30 Mtrs, IP67, PoE
- Supports Instastream technology, save disk space and bandwidth upto 70%
- Mobile Software: Android, iOS
- CMS Software: IVMS

**InstaStream**

# CP- VNC-T41R3M-D

## 4 MP WDR IR Array Bullet Camera - 30Mtr.

### Feature

Image Sensor  
 Minimum Illumination  
 Shutter Speed  
 White Balance  
 Lens  
 DORI Distance  
 Angle of View  
 Gain Control (AGC)  
 BLC  
 S/N Ratio  
 Video Compression  
 Video Streaming  
 Resolution  
 Frame Rate  
 Motion detection  
 Privacy Mask  
 ICR  
 ROI  
 Dewarping  
 Protocol  
 Ethernet  
 IR  
 OSD  
 Operating Temperature  
 Humidity  
 Casing  
 Power Source  
 Power Consumption

### Specification

1/3" 4MP Progressive scan CMOS  
 Colour: 0.03Lux (F2.0, AGC ON) 0Lux with IR on  
 Auto/Manual, 1~1/100000 s  
 Auto/Manual  
 3.6mm Lens (6mm Optional)  
 3.6mm- 81 Detect (m) , 32.4 Observe (m), 16.2 Recognize (m), 8.1 Identify (m)  
 6mm- 135 Detect (m) , 54 Observe (m), 27 Recognize (m), 13.5 Identify (m)  
 3.6mm- 86.4° (H), 43.6° (V), 112.3° (O), 6mm- 49.9° (H), 27° (V), 61.4° (O)  
 Auto/Manual  
 BLC/HLC/WDR(120dB)  
 >55dB  
 Ultra H.265/ H.265/H.264/MJPEG  
 Triple  
 2592x1520  
 Main Stream: 4MP (2592x1520), Max 20fps; 4MP (2560x1440), Max 25fps; 3MP (2048x1520),  
 Max 30fps; Sub Stream: 2MP (1920x1080), Max 30fps; Third Stream: D1 (720x576), Max 30fps  
 Up to 4 areas  
 Up to 8 areas  
 IR-cut filter with auto switch (ICR)  
 Up to 8 areas  
 Support  
 IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP,  
 UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, ONVIF (Profile S, Profile T), API  
 1 RJ45 10M/100M Base-TX Ethernet  
 IR Range of 30 Mtr.  
 Up to 8 OSDs  
 -35°C ~ 60°C (-31°F ~ 140°F)  
 ≤ 95% RH (non-condensing)  
 Metal  
 DC 12V±25%, PoE (IEEE 802.3af)  
 Max 6 W

 **CP- VNC-T41R3M-D****4 MP WDR IR Array Bullet Camera - 30Mtr.****Feature**

Weatherproof Standard

Dimension

Weight

**Specification**

IP67

157.3 × 62.4 × 63 mm (6.2" × 2.5" × 2.5")

0.45 kg