

CP- VNR-3432**32 Ch. 4K Network Video Recorder****Main Features**

- 32 Channel IP Camera Input
- Ultra H.265/ H.265/H.264 Video Formats
- Support 4K Resolution Upto 12MP Recording
- 320Mbps Incoming/ 320Mbps Outgoing Bandwidth
- Various fisheye dewarping modes for live view and playback for both web interface and GUIs
- Support 4 SATA HDDs up to 10TB Each, 3 USB Ports
- Support Multi-brand network cameras
- Mobile Software: Android, iOS
- CMS Software: IVMS



CP- VNR-3432

32 Ch. 4K Network Video Recorder

Feature

Processor
 Operating System
 IP Camera Input
 Two-way Talk
 User Interface
 HDMI/VGA Output
 Compression
 Recording Resolution
 Video Recording
 Video Display Split
 OSD
 Bit Rate
 Audio Input
 Audio Output
 Corridor Mode Screen
 Live view/Playback
 Capability
 Alarm Input
 Alarm Output
 Hard Disk
 ANR Technology
 Fisheye Dewarping Mode live and playback
 Trigger Events
 Cloud Upgrade
 Search Mode
 Playback
 Interface Ports
 Max User Account

Specification

Dual-core embedded processor
 Embedded LINUX
 32 channel
 1 channel, RCA
 GUI
 HDMI1/VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
 HDMI2: 4K (3840x2160)/60Hz, 4K (3840x2160)/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
 Ultra H.265/ H.265 / H.264
 12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
 320 Mbps
 1/4/8/9/16
 Camera Title, Time, Motion Detection, Recording
 Supports
 1 channel, RCA
 1 channel, RCA
 3/4/5/7/9/10/12/16/32
 12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
 3 x 12MP@25, 4 x 4K@30, 8 x 4MP@30, 16 x 1080p@30, 32 x 960p@25
 16 channel
 4 channel
 4 SATA ports, up to 10TB Each
 Supports
 Supports
 Recording, PTZ, Alarm Out, Video Push, Email, Snapshot, Buzzer, etc
 Supports
 Time/Date, Alarm, MD, Exact Search (By Minute/Second)
 16 Ch
 3 USB Port, 1 RS485
 128 users

CP- VNR-3432**32 Ch. 4K Network Video Recorder****Feature**

Ethernet
Protocols
Power Supply
Power Consumption
Working Temp
Working Humidity
Dimensions
Weight

Specification

2 RJ-45 10M/100M/1000M self-adaptive Ethernet Interfaces
P2P, UPnP, NTP, DHCP, PPPoE, ONVIF conformance: Profile S, Profile G, Profile T
12V DC
≤ 12 W (without HDD)
-10°C ~ + 55°C (+14°F ~ +131°F)
10% ~ 90%
44mm × 440mm × 344mm
≤ 3.14 Kg