

CP- UD-0212H-4K**Ultra-HD Network Video Decoder****Main Features**

- H.265/H.264/MJPEG/MPEG4/MPEG2 video decoding
- Ultra-high decoding ability, up to 12 Megapixels
- 2ch HDMI and 2ch DVI-I input, support 4K collection (HDMI)
- Support 1/4/9/16 display split
- Support audio, alarm, bi-directional talk, RS485
- Support redundant power, stable and reliable
- Splicing screens control for zoom/merge/roam/overlay

CP- UD-0212H-4K

Ultra-HD Network Video Decoder

Feature

Processor
 Operating System
 Slot
 User Interface
 Video Input
 Video Output
 Video Standard
 Display Resolution
 Collection Resolution
 Decoding Capacity Separately
 Decoding Resolution
 Total Video Decoding
 Audio Format
 Audio Output
 Bi-directional Talk
 Alarm Input/ Output
 Interface Ports
 Ethernet
 Power Supply
 Power Consumption
 Working Temp
 Dimensions
 Weight

Specification

Intel Embedded processor
 Embedded LINUX
 1 Main board, 2 Decoding board(6CH), 1 Decoding board(3CH), 1 Collection board, 2 Blank panel
 GUI
 2 HDMI, 2 DVI-I
 12ch HDMI
 H.265/H.264/MPEG2/MJPEG
 3840×2160/2560×1600/1920×1080/1280×1024/1280×720/1024×768
 3840×2160/1920×1080/1600×1200/1680×1050/1440×900/1400×1050/1366×768/1280×1024/1280×960/1280×800/1280×720/1152×864/1024×768/800×600, etc
 Port1,2,3 / Port4,5,6 / Port7,8,9/ Port10,11,12
 3CH@12MP/4CH@4K/8CH@5MP/10CH@3MP/16CH@1080P/ 36CH@720P/48CH@D1
 12MP/8MP/6MP/5MP/4MP/3MP/1080P/720P/960H/D1/HD1/2CIF/CIF/QCIF
 12CH@12MP/16CH@4K/32CH@5MP/40CH@3MP/64CH@1080P/144CH@720P/192CH@D1
 PCM/G711/AAC
 12ch HDMI
 1 Pair 3.5mm jack (2.0V Line in/50mV Mic in/10KΩ, 2.0V/16Ω out)
 2CH/1CH(30V DC 1A, 125V AC 0.5A)
 3 RS232(1 DB9, 2 RJ45) , 1 RS485, 3 USB Ports (2 USB3.0, 1 USB2.0)
 2 RJ45 network port (10M/100M/1000M)
 AC100-127V, 200-240V, 47Hz-63Hz
 ≤180W
 -10°C ~+55°C / 10~95%RH / 86~106kpa
 440×436.6×110mm
 11.25kg