

**CP- UNC-TE4K081ZL10E-VMD****4K WDR IR Network Bullet Camera - 100 Mtr.****Main Features**

- 1/2.5" 8MP PS CMOS Image Sensor
- 15fps@4K(3840×2160),25/30fps@3Mp(2304×1296)
- H.265 and H.264 Triple-stream encoding
- WDR, Day/Night (ICR), 3D-DNR, ROI, AWB, AGC, BLC, HLC
- 7mm ~35mm motorized lens
- IR Range of 100 Mtrs, IP67, IK10, SD Card, ePoE
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



# CP- UNC-TE4K081ZL10E-VMD

## 4K WDR IR Network Bullet Camera - 100 Mtr.



### Feature

Image Sensor  
 Effective Pixels  
 Minimum Illumination  
 Shutter Speed  
 White Balance  
 Lens  
 Gain Control (AGC)  
 Video Compression  
 Angle of View  
 Back Light Compensation  
 S/N Ratio  
 Video Streaming  
 Video Output  
 Resolution  
 Digital Zoom  
 Motion detection  
 Privacy Mask  
 ICR  
 ROI  
 Audio Input  
 Audio Output  
 Audio Compression  
 Alarm IN  
 Alarm Out  
 Bit Rate  
 Protocol  
 Smart Detection  
 Ethernet

### Specification

1/2.5" 8MP progressive scan CMOS  
 3840(H)x2160(V)  
 0.05Lux/F1.4 (Color,1/3s,30IRE), 0.2Lux/F1.4 (Color,1/30s,30IRE), 0Lux/F1.4(IR on)  
 Auto/Manual, 1/3~1/100000s  
 Auto/Natural/Street Lamp/Outdoor/Manual  
 7mm~35mm  
 Auto/Manual  
 H.265+/H.265/H.264+/H.264  
 H:38°~14°, V:22°~8°  
 BLC / HLC / WDR  
 More than 50dB  
 Main Stream: 4K(1~15fps)/3M(1~25/30fps), Sub Stream: D1(1~25/30fps), Third Stream: 720P(1~25/30fps)  
 1 Port (For adjustment only)  
 4K(3840x2160)/ 6M(3072x2048)/5M(3072x1728)/ 5M(2592x1944)/ 4M(2688x1520)/ 3M(2048x1536)/ 3M(2304x1296)/ 1080P(1920x1080)/1.3M(1280x960)/ 720P(1280x720)/ D1(704x576/704x480)  
 16x  
 Off / On (4 Zone, Rectangle)  
 Off / On (4 Area, Rectangle)  
 Auto (ICR)/Color/B/W  
 Off / On (4 Zone)  
 1 Channel  
 1 Channel  
 G.711a/ G.711Mu/ AAC/ G.726  
 2 channel In: 5mA 5VDC  
 1 channel Out: 300mA 12VDC  
 H.264: 24K ~ 10240Kbps, H.265: 14K ~ 9984Kbps  
 HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP;FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP; NTP; Bonjour; 802.1x; Multicast; ICMP;IGMP; SNMP, ONVIF, PSIA, CGI  
 Tripwire, Intrusion, Object Abandoned/Missing, Face Detection  
 RJ-45 (10/100Base-T)



**CP- UNC-TE4K081ZL10E-VMD****4K WDR IR Network Bullet Camera - 100 Mtr.****Feature**

User Account

Smart Phone

IR

Micro SD

Operating Temperature

Power Source

Power Consumption

Weatherproof Standard

Casing

Dimension

Weight

**Specification**

20 Users

iPhone, iPad, Android

IR Range of 100 Mtr.

Micro SD card 128GB

-30° C ~ +60° C, Less than 95% RH

DC12V, ePoE

&lt;12.95W

IP67 &amp; IK10

Metal

273.2mm x 95mm x 95mm

1.11 Kg