


CP- UNC-VE41ZL4E-VMD**4MP WDR AI IR Vandal Dome Camera - 40Mtr.****Main Features**

- 1/1.8" 4MP PS CMOS Image Sensor (1.411 cm)
- 25/30fps@(2688 × 1520), 50/60fps@1080P(1920 × 1080)
- Instastream, H.265 and H.264+ triple-stream encoding
- WDR(140dB), Day/Night (ICR), 3D-DNR, Defog, EIS, AWB, AGC, BLC, HLC
- 2.7 -12mm Motorized Lens
- IR Range of 40 Mtrs, Micro SD Card, IP67, IK10, PoE
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



CP- UNC-VE41ZL4E-VMD

4MP WDR AI IR Vandal Dome Camera - 40Mtr.

Feature

Image Sensor
 Minimum Illumination
 Effective Pixels
 Shutter Speed
 White Balance
 Lens
 Gain Control (AGC)
 Video Compression
 Back Light Compensation
 Angle of View
 S/N Ratio
 Video Streaming
 Resolution
 Motion detection
 Privacy Mask
 Face Detection
 Audio Input
 Audio Output
 Audio Compression
 Alarm IN
 Alarm Out
 Protocol

Specification

1/1.8" 4Megapixel progressive scan CMOS (1.411 cm)
 0.003 Lux@F1.8
 2688 (H) × 1520 (V)
 Auto/Manual, 1/3 s–1/100000 s
 Auto/Natural/Street Lamp/Outdoor/Manual
 2.7 -12mm Motorized Lens
 Auto/Manual
 Instastream/H.265/H.264+/H.264/H.264B/ H.264H/ MJPEG (sub stream)
 BLC/HLC/WDR (140 dB)
 H: 114°–47°, V: 62°–26°
 > 56 dB
 Main Stream: 2688 × 1520 (1 fps–25/30 fps) 2560 × 1440 (1 fps–25/30 fps) 1920 × 1080 (1 fps–50/60 fps) Sub Stream: D1 (1 fps–25/30 fps) D1 (1 fps–50/60 fps) Third Stream: 1080P (1 fps–16 fps)
 2688 × 1520/2560 × 1440/2304 × 1296/1080P (1920 × 1080)/1.3M (1280 × 960)/720P (1280 × 720)/D1 (704 × 576/704 × 480)/VGA (640 × 480)/CIF (352 × 288/352 × 240)
 Off/On (4 Zone, Rectangle)
 Off/On (4 Area, Rectangle)
 Face detection; track; optimization; snapshot; report high quality picture; face enhancement; face exposure; face attribute extract, 6 attributes and 8 expressions: Gender, age, glasses, expressions (anger, calm, happiness, sadness, disgust, surprise, confusion and fear), mask, beard; face matting setting: face, single inch photo; three snapshot methods: real-time snapshot, optimization snapshot, quality priority; face angle filter; optimization time setting.
 1 Channel
 1 Channel
 G.711a, G.711Mu, G.726, AAC, G.723
 1 channel In: 5mA 5V DC
 1 channel Out: 300mA 12V DC
 IPv4; IPv6; HTTP; HTTPS; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; PPPoE; 802.1x; SNMP; ONVIF (Profile S/Profile G/Profile T), CGI, Milestone, Genetec, Instaon

CP- UNC-VE41ZL4E-VMD

4MP WDR AI IR Vandal Dome Camera - 40Mtr.

Feature	Specification
ICR	Auto (ICR)/Color/B/W
Smart Detection	Object Abandoned/Missing, Heat Map
Alarm Event	No SD card; SD card full; SD card error; network disconnection; IP conflict; illegal access; motion detection; video tampering; Defocus Detection; scene changing; intrusion; tripwire; abandoned object; missing object; fast moving; parking detection; loitering detection; people gathering; audio detection; people counting; face detection; People counting in area; Stay alarm; People No. exception detection; Queue Management
Ethernet	RJ-45 (10/100Base-T)
Event Trigger	Motion detection, Video tampering, Scene changing, Network disconnection, IP address conflict, Illegal Access, Storage anomaly
People Counting	Support the counting of enter number, leave number, and pass number, and displaying and outputting yearly/monthly/daily reports. Support the counting of number in area, and 4 rules configuration. Count number of people or stay time and link alarm. Support queue management, and 4 rules configuration. Count number of people or stay time and link alarm.
Perimeter Protection	Tripwire; intrusion; fast moving (the three functions support the classification and accurate detection of vehicle and human); loitering detection; people gathering; parking detection
User Account	20 Users
Smart Phone	iPhone, iPad, Android Phone
IR	IR Range of 40 Mtr.
Micro SD	NAS; FTP; SFTP, Micro SD card (512GB)
Operating Temperature	-30°C to +60°C (-22°F to +140°F)/Less than 95% RH
Power Source	DC 12V (±30%), AC 24V (±30%), PoE (802.3af), ePoE
Power Consumption	<12.4W
Weatherproof Standard	IP67 & IK10
Dimension	Φ159.0 mm × 117.9 mm (6.26" × 4.64")
Casing	Metal
Weight	0.95 kg