

CP- UNR-108F1**8 Ch. Network Video Recorder****Main Features**

- 8 Ch. with 1080p Realtime Live View
- H.264/MJPEG dual codec decoding
- Max 56Mbps incoming bandwidth
- Support 1 SATA HDDs up to 4TB, 2 USB2.0
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras, Support P2P (QR code Scan)
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



CP- UNR-108F1

8 Ch. Network Video Recorder



Feature

Processor
IP Camera Input
Operating System
User Interface
Video Output
Compression
Video Resolution
Video Recording
Video Display Split
Motion Detection
Video Loss
Camera Blank
Smart Phone
Hard Disk
Trigger Events
Recording Mode
Search Mode
Playback
Backup Mode
Interface Ports
Record Interval
Max User Account
Ethernet
Protocols
Power Supply
Power Consumption
Working Temp
Dimensions
Weight

Specification

Dual-core embedded processor
8 channel
Embedded LINUX
GUI
1 HDMI, 1 VGA
H.264 / MJPEG
1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768
Max 56 Mbps
1/4/8/9
MD Zones: 396(22×18).
Supports
Supports
iPhone, iPad, Android, Windows Phone
1 SATA ports, up to 4TB
Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen
Manual, Schedule (Regular (Continuous), MD, Alarm), Stop
Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
USB Device / Internal SATA burner/ Network
1 HDMI, 1 VGA, 2 USB2.0, 1 RJ45
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
128 users
1 RJ-45 port (10/100M)
HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.4
Single, DC5V/2A
<2W (without HDD)
-10 ~+55°C / 10~90%RH / 86~106kpa
192mm×128mm×36mm
320g (without HDD)

