

CP- UVR-0808F8**8 Ch. 1080P HDCVI DVR****CP PLUS**
CORAL**Main Features**

- Up to 8 cameras with 1080p Realtime Preview
- H.264 dual-stream Video Compression
- HDMI / VGA / TV Simultaneous Video Output
- Support 8 SATA HDD (8HDD or 6HDD + 1 CD/DVDRW), up to 32TB, 1 eSATA up to 16TB, 4 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



CP- UVR-0808F8

8 Ch. 1080P HDCVI DVR



Feature

Processor
 Operating System
 Two-way Talk
 User Interface
 Video Input
 Video Output
 Video Standard
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Privacy Masking
 Audio Input
 Audio Output
 Motion Detection
 Video Loss
 Camera Blank
 Alarm Input
 Alarm Output
 Smart Phone
 Hard Disk
 Trigger Events
 Recording Mode
 Search Mode
 Playback
 Backup Mode
 Max User Account
 Interface Ports
 Record Interval

Specification

Embedded processor
 Embedded LINUX
 Reuse audio input/output channel 1
 GUI
 8 channel, BNC
 1 HDMI, 1 VGA ,1 BNC
 NTSC(525Line, 60f/s), PAL(625Line, 50f/s)
 H.264 / G.711
 1080P(1920×1080/1920×900)/720P(1280×720/1280×600)/960H(960×576/960×480)/
 D1/4CIF(704×576/704×480) / CIF(352×288/352×240) / QCIF(176×144/176×120)
 Main Stream: 1080P/720P/960H/D1/HD1/2CIF/CIF(1~25/30fps), Extra Stream: CIF/QCIF
 1/4/8/9
 4 rectangular zones (each camera)
 8 channel, RCA
 1 channel, RCA
 Supports
 Supports
 Supports
 8 Channel
 6 Channel
 iPhone, iPad, Android, Windows Phone
 8 SATA port (6 HDD + 1 CD/DVDRW), up to 32TB, 1 eSATA port (Max 4 SATA HDDs), up to
 Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips
 Manual, Schedule(Regular(Continuous), MD), Stop
 Time/Date, MD & Exact search (accurate to second)
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file,Next camera, Previous
 camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom
 USB Device / Network
 128 users
 1 RS485, 1 RS232, 1RS422, 4 USB2.0
 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

CP- UVR-0808F8**8 Ch. 1080P HDCVI DVR****Feature**

Ethernet
Protocols
Power Supply
Power Consumption
Working Temp
Dimensions
Weight

Specification

RJ-45 port (10/100M/1000M)
HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP
AC 100~240 V, 50/60 Hz
40W(without HDD)
-10 ~+55°C / 10~90%RH / 86~106kpa
440mm× 460mm× 89mm
6.5KG(without HDD)