

CP- UNP-3020L20DA**2MP 30x WDR IP IR PTZ Dome Camera****ORANGE****Main Features**

- 1/1.9" CMOS Image sensor
- Max 60fps@720P and 30fps@1080P resolution
- Powerful 30x Optical and 16x Digital zoom
- Defog, WDR, EIS, ROI, Day/Night(ICR), Ultra DNR
- Up to 300 Presets, 8 Tour, 5 Pattern, 5 Auto scan
- Max 240°/s pan speed, 360° endless pan rotation
- Auto-tracking and IVS, IR Range of 200 Mtr.
- Built-in 7/2 alarm in/out, IP67, IK10, Hi-PoE, Micro SD
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



CP- UNP-3020L20DA

2MP 30x WDR IP IR PTZ Dome Camera



Feature

Image Sensor
 Effective Pixels
 Video Output
 S/N Ratio
 Minimum Illumination
 Focal Length
 Focus Control
 White Balance
 Angle of View
 Close Focus Distance
 Electronic Shutter
 AGC control
 Back Light Compensation
 Optical Zoom
 Digital Zoom
 Pan Travel
 Tilt Travel
 Presets
 Preset Speed
 Privacy Masking
 Special Features
 Power up Action
 Idle Motion
 Time Task
 Day/Night: IR Cut Filter
 Video Compression
 Video Streaming
 Audio Compression
 Auto Tracking
 Audio Streaming

Specification

1/1.9" CMOS
 1944(H) x 1092(V), 2 Megapixels
 BNC(1.0Vp-p/75Ω), PAL / NTSC
 More than 56dB
 Color: 0.002Lux@F1.6; B/W: 0.0002Lux@F1.6; 0Lux (IR on)
 6mm~180mm
 Auto / Manual
 Auto, ATW, Indoor, Outdoor, Manual
 H: 51.2° ~ 1.8°
 100mm~ 1000mm
 1/1 ~ 1/30,000s
 Auto / Manual
 BLC / HLC / WDR
 30x
 16x
 0° ~ 360° endless, Pan Speed: 0.1° ~ 240°/sec
 -20° ~ 90°, auto flip 180°, Tilt Speed: 0.1° ~ 120°/sec
 300
 Pan: 240° /s; Tilt: 200° /s
 Up to 24 areas
 IR Range of 200 Mtr., Up to 255 Presets, 8 Tour, 5 Pattern, 5 Auto scan
 Auto restore to previous PTZ and lens status after power failure
 Activate Preset/ Pan/ Scan/ Tour/ Pattern if there is no command in the specified period
 Auto activation of Preset/Pan/Scan/Tour/Pattern by preset-time
 Auto(ICR) / Color / B/W
 H.264 / MJPEG
 Main Stream: 1080P/ D1 (1 ~ 25/30fps), 720P(1~50/60fps), Sub Stream1: D1/CIF(1 ~ 25/30fps), Sub Stream 2: 720P/D1/ CIF (1 ~ 25/30fps)
 G.711a / G.711u(32kbps)/ PCM(128kbps)
 Single-scene, multiple-scene, panorama-scene
 1/1 channel In/Out

IVS
 Tripwire, Intrusion, Cross Warning Zone, Perimeter Protection, Loitering Detection, Abandoned Object Detection, Missing Object Detection, Illegal Parking, Fast Moving and etc.

CP- UNP-3020L20DA

2MP 30x WDR IP IR PTZ Dome Camera



Feature

Networking

Protocols

Tracking Trigger Mode

Tracking Trigger Event

Alarm

Max Remote Users

Smart Phone

Operating Temperature

Memory Slot

Weather Proof Standard

Dimension

Weight

Power Source

Power Consumption

Specification

RJ-45 (10/100Base-T), 1RS485

IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S

Manual / Auto (alarm triggered)

Targeting, Zoom, Tracking, Recording, Snapshot, Alarm and etc.

7/2 channel In/Out

20 users

iPhone, iPad, Android, Windows Phone

-40°C ~ 70°C / Less than 90% RH

Micro SD, Max 128GB

IP67, IK10

Φ252(mm) x 384.3 (mm)

6.75 kg

AC24V/3A(±25%), Hi-POE

20W, 43W (IR on, Heater on)