

CP- UNR-432T8-P16**32 Ch. Network Video Recorder with 16 PoE Ports****Main Features**

- 32 Ch. with 1080p Realtime Live View
- H.264/MJPEG dual codec decoding
- Up to 5Mp resolution preview&playback
- Max 200Mbps incoming bandwidth
- Support 8 SATA HDDs up to 32TB, 1 eSATA up to 16TB,3 USB(1 USB3.0)
- HDMI / VGA / TV simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.3 conformance, 16 Ports PoE(IEEE802.3at)
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



CP- UNR-432T8-P16

32 Ch. Network Video Recorder with 16 PoE Ports

Feature

Processor
 Operating System
 IP Camera Input
 Two-way Talk
 User Interface
 Video Output
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Motion Detection
 Video Loss
 Camera Blank
 Alarm Input
 Alarm Output
 Hard Disk
 Smart Phone
 Trigger Events
 Recording Mode
 Search Mode
 Playback
 Backup Mode
 Max User Account
 Interface Ports
 Record Interval
 Ethernet
 Protocols
 Power Supply
 Power Consumption

Specification

Dual-core embedded processor
 Embedded LINUX
 32 channel
 1 channel Input, 1 channel Output, RCA
 GUI
 1 HDMI, 1 VGA, 1 BNC
 H.264 / MJPEG
 2560 × 1920, 2048 × 1536, 1920 × 1080, 1280 × 1024, 1280 × 720, 1024 × 768
 Max 128 Mbps
 1/4/8/9/16
 MD Zones: 396(22×18).
 Supports
 Supports
 16 channel
 4 channel
 8 SATA ports, up to 32TB, Raid (Redundancy), 1 eSATA port
 iPhone, iPad, Android, Windows Phone
 Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen
 Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
 Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
 USB Device / Internal SATA burner/ Network
 128 users
 1 HDMI, 1 VGA, 3 USB2.0, 1 RS485, 1 RS232, 1 RJ45, 16 PoE Ports
 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
 1 RJ-45 port (10/100M/1000M)
 HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.3
 AC 100V~240V, 50/60HZ
 40W(without HDD)

 **CP- UNR-432T8-P16****32 Ch. Network Video Recorder with 16 PoE Ports****Feature**

Working Temp

Dimensions

Weight

Specification

-10 ~+55°C / 10~90%RH / 86~106kpa

440mm×460mm×89mm

6.5 Kg (without HDD)