

**CP- UNR-404T2-M11****4 Channel PoE Mobile Standalone NVR****Main Features**

- Up to 4 channel 1080P cameras realtime live view
- Max 200Mbps Recording rate
- Multi-information display and recording: Car Number, Time, Channel, GPS, Speed, support freely setting of overlay and recording
- Built-in module GPS, 3G, Wi-Fi
- 4 PoE Ports, Onvif Version 2.3 conformance
- Aviation connectors adopted ensuring signal stability
- Support 2 SATA HDDs upto 4TB, 1 eSATA, 3 USB2.0
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro

# CP- UNR-404T2-M1 1

## 4 Channel PoE Mobile Standalone NVR

### Feature

Processor  
Operating System  
Two-way Talk  
Video Input  
Video Output  
Compression  
Video Resolution  
Video Recording  
Video Display Split  
Privacy Masking  
Audio Input  
Audio Output  
Motion Detection  
Video Loss  
Camera Blank  
Alarm Input  
Alarm Output  
Hard Disk  
Smart Phone  
SD Card  
Trigger Events  
Recording Mode  
Search Mode  
  
Playback  
  
Backup Mode  
Max User Account  
Record Interval  
Interface Ports  
Wi-Fi  
PoE  
G-Sensor

### Specification

Dual-core embedded processor  
Embedded Linux  
1 channel Input, 1 channel Output  
4Ch.  
1 HDMI, 1 VGA, 2 TV  
H.264 /H.265(optional)/ G711 / PCM  
1920×1080, 1280×1024, 1280×720, 1024×768  
Max 200 Mbps  
1/4  
4 rectangular zones (each camera)  
1 Ch.  
1 Ch.  
Zones: 396(22×18), IVS (optional)  
Supports  
Supports  
8 channel  
3 channel  
2 SATA ports upto 4 TB, 1 eSATA  
iPhone, iPad, Android Phone  
SD card supports  
Recording, PTZ, Tour, Alarm, Email, FTP, Buzzer & Screen tips  
Manual, Schedule (Regular (Continuous), MD, Alarm), Stop  
Time/Date, Alarm, Motion Detection & Exact search (accurate to second)  
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom  
USB Device/eSATA Device/Network/Internal HDD  
128 users  
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec  
3 USB 2.0, 1 RS232, 1 RJ45, 1 RS485, 1 eSATA, 2 Sim slots (optional)  
Built-in 3G & Wi-Fi module  
4 ports(IEEE802.3af/at)  
Support

**CP- UNR-404T2-M11****4 Channel PoE Mobile Standalone NVR****Feature**

GPS

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Working Humidity

Dimensions

Weight

**Specification**

Built-in high accurate GPS module

RJ-45 port (10/1000M)

TCP/IP, UDP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Email, Alarm Server

6V~36V

≤10W

-30°C ~+60°C / 10%~95%RH

5Hz~300Hz: X / Y / Z each direction 8 hours, 5Hz~11Hz: Vibration amplitude 10mm,  
11Hz~300Hz: 50m/s<sup>2</sup>

180mm × 208mm × 100mm

3 KG (Without HDD)