

CP- UNR-404T2-M11**4 Channel PoE Mobile Standalone DVR****Main Features**

- Up to 4 channel 1080P cameras realtime live view
- Max 200Mbps Recording rate
- Multi-information display and recording: Car Number, Time, Channel, GPS, Speed, support freely setting of overlay and recording
- Built-in module GPS, 3G, Wi-Fi
- 4 PoE Ports, Onvif Version 2.3 conformance
- Aviation connectors adopted ensuring signal stability
- Support 2 SATA HDDs upto 4TB, 1 eSATA, 3 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro

CP- UNR-404T2-M1 1

4 Channel PoE Mobile Standalone DVR

Feature

Processor
Operating System
Two-way Talk
Video Input
Video Output
Compression
Video Resolution
Video Recording
Video Display Split
Privacy Masking
Audio Input
Audio Output
Motion Detection
Video Loss
Camera Blank
Alarm Input
Alarm Output
Hard Disk
Smart Phone
SD Card
Trigger Events
Recording Mode
Search Mode

Playback

Backup Mode
Max User Account
Record Interval
Interface Ports
Wi-Fi
PoE
G-Sensor

Specification

Dual-core embedded processor
Embedded Linux
1 channel Input, 1 channel Output
4Ch.
1 HDMI, 1 VGA, 2 TV
H.264 /H.265(optional)/ G711 / PCM
1920×1080, 1280×1024, 1280×720, 1024×768
Max 200 Mbps
1/4
4 rectangular zones (each camera)
1 Ch.
1 Ch.
Zones: 396(22×18), IVS (optional)
Supports
Supports
8 channel
3 channel
2 SATA ports upto 4 TB, 1 eSATA
iPhone, iPad, Android, Windows Phone
SD card supports
Recording, PTZ, Tour, Alarm, Email, FTP, Buzzer & Screen tips
Manual, Schedule (Regular (Continuous), MD, Alarm), Stop
Time/Date, Alarm, Motion Detection & Exact search (accurate to second)
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
USB Device/eSATA Device/Network/Internal HDD
128 users
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
3 USB 2.0, 1 RS232, 1 RJ45, 1 RS485, 1 eSATA, 2 Sim slots (optional)
Built-in 3G & Wi-Fi module
4 ports(IEEE802.3af/at)
Support

 **CP- UNR-404T2-M11****4 Channel PoE Mobile Standalone DVR****Feature**

GPS

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Working Humidity

Dimensions

Weight

Specification

Built-in high accurate GPS module

RJ-45 port (10/1000M)

TCP/IP, UDP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Email, Alarm Server

6V~36V

≤10W

-30°C ~+60°C / 10%~95%RH

5Hz~300Hz: X / Y / Z each direction 8 hours, 5Hz~11Hz: Vibration amplitude 10mm,
11Hz~300Hz: 50m/s²

180mm × 208mm × 100mm

3 KG(Without HDD)