

**CP- UNC-TB30FL6S-M-V2****3 MP HD IR Bullet Camera - 60Mtr.****Main Features**

- 1/3" 3MP PS CMOS Image Sensor
- Max 20fps@3M and 25/30fps@1080P
- H.264 and MJPEG dual-stream encoding
- DWDR, Day/Night (ICR), 3DNR, AWB, AGC, BLC
- 2.7 -12mm Varifocal Lens
- IR Range of 60 Mtrs, IP67,PoE, SD Card
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro



# CP- UNC-TB30FL6S-M-V2

## 3 MP HD IR Bullet Camera - 60Mtr.



### Feature

Image Sensor

Effective Pixels

Minimum Illumination

Shutter Speed

White Balance

Gain Control (AGC)

Lens

Video Compression

Back Light Compensation

S/N Ratio

Video Streaming

Resolution

Privacy Mask

ICR

Bit Rate

Protocol

Ethernet

User Account

Smart Phone

IR

Micro SD

Operating Temperature

Power Source

Power Consumption

Weatherproof Standard

Dimension

Weight

### Specification

1/3" 3MP Progressive scan CMOS

2304(H)x1296(V)

0.01Lux/F1.4(Color), 0Lux/F1.4(IR on)

Auto/Manual, 1/3(4)~1/100000s

Auto/Manual

Auto/Manual

2.7 -12mm Varifocal Lens

H.264/ H.264H/ MJPEG

BLC/ HLC/ DWDR

More than 50dB

Main Stream: 3M(1 ~ 20fps)/1080P (1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)

3M(2304x1296) / 1080P(1920x1080) / 1.3M(1280x960) / 720P(1280x720) / D1 (704x576/704x480) / CIF(352x288/352x240)

Up to 4 areas

Auto (ICR)/Color/B/W

H.264H: 40K ~ 8192Kbps

IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF, PSIA, CGI

RJ-45 (10/100Base-T)

20 Users

iPhone, iPad, Android Phone

IR Range of 60 Mtr.

Micro SD , Max 128GB

-30°C~+60°C , Less than 95%RH

DC12V, PoE (802.3af)

<5.5W

IP67

72mmx80mmx212.8mm

0.65kg