

CP- UNR-4K4328-V2**32 Ch. H.265 4K Network Video Recorder****Main Features**

- Up to 32 channel IP camera input
- H.265/H.264 dual codec decoding
- Up to 8Mp resolution preview and playback
- Max 200Mbps incoming bandwidth
- Support 8 SATA HDDs up to 48TB, 3USB(1 USB3.0)
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



CP- UNR-4K4328-V2**32 Ch. H.265 4K Network Video Recorder****Feature**

Processor
IP Camera Input
Operating System
Two-way Talk
User Interface
Video Output
Compression
Video Resolution
Video Recording
Video Display Split
Motion Detection
Video Loss
Camera Blank
Alarm Input
Alarm Output
Hard Disk
Smart Phone
Trigger Events
Recording Mode
Search Mode
Playback
Backup Mode
Interface Ports
Max User Account
Record Interval
Ethernet
Protocols
Power Supply

Specification

Dual-core embedded processor
32 channel
Embedded LINUX
1 channel Input, 1 channel Output, RCA
GUI
1 HDMI, 1 VGA
H.265 / H.264
3840× 2160, 1920× 1080, 1280× 1024, 1280× 720, 1024× 768
200Mbps
1/4/8/9/16
MD Zones: 396(22×18).
Supports
Supports
16 Channel, Low Level Effective, Green Terminal Interface
4 Channel, NO/NC Programmable, Green Terminal Interface
8 SATA III ports, up to 48TB
iPhone, iPad, Android Phone
Recording, PTZ, Tour, Alarm out, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips
Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Tampering, Video Loss), Stop
Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
USB Device/Network
1 HDMI, 1 VGA, 3 USB Ports (2 USB2.0, 1 USB3.0), 1 RS485, 1 RS232
128 users
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
2 RJ-45 Ports
HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, SNMP, FTP, IP Search, ONVIF 2.4, SDK, CGI Conformant
AC100V ~ 240V, 50 ~ 60 Hz





CP- UNR-4K4328-V2

32 Ch. H.265 4K Network Video Recorder



Feature

Power Consumption

Working Temp

Dimensions

Weight

Specification

<12W (Without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

440mm x 450.1mm x 95mm

5.2kg (without HDD)



**Product casing and specifications are subject to change without prior notice*