

CP- UNR-408T2-MF**8 Channel PoE Mobile Standalone DVR****Main Features**

- Up to 8 channel 1080P Cameras Realtime live view
- H.264 / MJPEG dual codec decoding
- Max 200 Mbps recording rate
- Built-in 3G/4G/Wi-Fi module (optional)
- 8 PoE Ports, Support 2 SATA HDDs, 2 USB2.0
- Support 2 SATA HDDs, 2 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



CP- UNR-408T2-MF

8 Channel PoE Mobile Standalone DVR



Feature

Processor
Operating System
Two-way Talk
Video Input
Video Output
Video Standard
Compression
Video Resolution
Video Recording
Video Display Split
Privacy Masking
Audio Input
Audio Output
Motion Detection
Video Loss
Camera Blank
Alarm Input
Alarm Output
Smart Phone
Hard Disk
SD Card
Trigger Events
Recording Mode
Search Mode
Playback
Backup Mode
Record Interval
Max User Account
Interface Ports
Wi-Fi

Specification

Dual-core embedded processor
Embedded Linux
1ch Mic in, 1ch Mic out (aviation connector)
8 channel
1 HDMI, 1VGA, 2TV
PAL: 625 Lines, 50f/s; NTSC: 525 Lines, 60f/s
H.264 / G711A
1920×1080, 1280×1024, 1280×720, 1024×768
Max 200 Mbps
1/4/8/9
4 rectangular zones (each camera)
8 Ch.
1 Ch.
Zones: 396(22×18)
Supports
Supports
8 channel
2 channel
iPhone, iPad, Android, Windows Phone
2 SATA ports up to 4TB, 1 eSATA port
1 SD card
Recording, PTZ, Tour, Alarm out, Email, FTP, Snapshot, Buzzer & Screen tips
Manual, Schedule (Regular (Continuous), MD, Alarm), Stop
Time/Date, Alarm, Motion Detection & Exact search (accurate to second)
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
USB Device / eSATA Device / Network / Internal HDD
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
128 users
3 USB 2.0, 1 RS232, 1 RJ45, 1 RS485, 1 eSATA, Supports G-Sensor, UPS, CAN Port
Built-in 3G / Wi-Fi module (optional)



CP- UNR-408T2-MF

8 Channel PoE Mobile Standalone DVR



Feature

GPS
Ethernet
Protocols
Power Supply
Power Consumption
Working Temp
Dimensions
Weight

Specification

GPS / BDS (optional)
RJ-45 port (10/100M)
HTTP, IPv4, TCP/IP, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, FTP, IP Filter
6V~36V
≤15W
-10°C ~+60°C / 10%~95%RH / 86~106kpa
180mm × 208mm × 100mm
3 KG (Without HDD)

