

CP- UNP-M3020L15

2 MP Full HD Network Mobile Positioning System



Main Features

- 1/2.8" Exmor CMOS Image Sensor
- 2MP Image Quality
- Powerful 30x Optical Zoom
- WDR (120dB), 2D/3D DNR, ROI, EIS, Defog, BLC,HLC
- Pan range: 360° endless, speed up to 60°/s
- Up to 256Presets, 4Tour, 4Pattern, 4Auto scan
- IR Distance up to 150 Mtr., IP66
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



CP- UNP-M3020L15

2 MP Full HD Network Mobile Positioning System



Feature

Image Sensor
Effective Pixels
Min Illumination
S/N Ratio
Focal Length
Focus Control
White Balance
Angle of View
Electronic Shutter
AGC control
Back Light Compensation
Optical Zoom
Digital Zoom
Pan Travel
Tilt Travel
Presets
Preset Accuracy
Special Features
Privacy Masking
Day/Night: IR Cut Filter
Video Compression
Video Streaming
Watermark
Motion Detection
Dynamic Noise Reduction
Networking
Protocols
Max Remote Users
Smart Phone
Operating Temperature

Specification

1/2.8" Exmor CMOS
1944(H) x 1092(V), 2 Megapixels
Color: 0.005lux, F1.6B/W, 0.0005lux, F1.6
More than 50dB
4.3mm ~ 129mm
Auto / Manual
Auto, ATW, Indoor, Outdoor, Manual
H: 65.1°~2.34
Auto/ Manual, 1/1 ~ 1/30,000s
Auto / Manual
WDR(120dB) / BLC / HLC
30x
16x
360° endless, 0.1° ~ 60°/sec;
-90° ~ 90°, 0.1° ~ 30°/sec
256
±0.02°
Up to 256 Presets, 4Tour, 4 Pattern, 4 Auto scan, Preset Auto-Calibration, Remote P/T/Z Re-set, Wiper, IR Range of 150 Mtr.
Up to 24 areas
Auto (ICR) / Color / B/W
H.265 / H.264 / MJPEG
Main Stream:25/30fps@1080P /720P, Sub Stream: 25/30fps@D1/CIF
Supports
Supports
2D/3D
RJ-45 (10/100Base-T)
IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x, ONVIF Profile S
20 users
iPhone, iPad, Android, Windows Phone
-30°C ~ 65°C / Less than 90% RH



CP- UNP-M3020L15

2 MP Full HD Network Mobile Positioning System



Feature

Weather Proof Standard

Weight

Regulatory

Power Source

Power Consumption

Specification

IP66, All-metal aluminum alloy, 6000V anti-lightning surge

8.5Kg;

CE, FCC, RoHS and EN50155

DC 8V~36V

<60W