

CP- UNP-M3020L15**2 MP Full HD Network Mobile Positioning System****Main Features**

- 1/2.8" CMOS Image Sensor
- 2MP Image Quality
- Powerful 30x Optical Zoom
- Max. 25/30fps@1080P, 25/30/50/60fps@720P
- WDR (120dB), 2D/3D DNR, ROI, EIS, Defog, BLC,HLC
- Pan range: 360° endless, speed up to 60°/s
- Up to 300 Presets, 8 Tour, 5 Pattern, Auto scan, Auto Pan
- IR Distance up to 150 Mtr., IP66
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro



CP- UNP-M3020L15**2 MP Full HD Network Mobile Positioning System****Feature**

Image Sensor
Effective Pixels
Min Illumination
S/N Ratio
Focal Length
Focus Control
White Balance
Angle of View
Electronic Shutter
AGC control
Back Light Compensation
Optical Zoom
Digital Zoom
Pan Travel
Tilt Travel
Presets
Preset Speed
Special Features
Privacy Masking
Day/Night: IR Cut Filter
Video Compression
Video Streaming
Motion Detection
Region of Interest
Dynamic Noise Reduction
Networking
Protocols
Memory

Specification

1/2.8" CMOS
1920(H) x 1080(V), 2 Megapixels
Color: 0.005lux, F1.6B/W, 0.0005lux, F1.6
More than 55dB
4.5mm ~ 135mm
Auto / Manual
Auto, ATW, Indoor, Outdoor, Manual
H: 67.8°~2.4°
Auto/ Manual, 1/1 ~ 1/300,000s
Auto / Manual
BLC / HLC / WDR (120dB)
30x
16x
360° endless, 0.1° ~ 60°/sec;
-90° ~ 90°, 0.1° ~ 30°/sec
300
Pan:60° /s; Tilt: 30° /s
Up to 300 Presets, 8 Tour, 5 Pattern, Auto scan, Auto Pan, Defog, EIS, IR Range of 150 Mtr.
Up to 24 areas
Auto (ICR) / Color / B/W
H.265 / H.264 / MJPEG
Main Stream: 1080P(1~50/60fps), 1.3M/720P(1 ~ 25/30fps) , Sub Stream: D1/CIF (1~25/30fps), Sub stream2: 1080P/1.3M/720P(1 ~ 25/30fps)
Supports
Supports
2D/3D
RJ-45 (10/100Base-T)
IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x, ONVIF, PSIA, CGI
SD Card upto128GB

CP- UNP-M3020L15**2 MP Full HD Network Mobile Positioning System****Feature**

Max Remote Users
Auto Tracking
Smart Detection
Smart Phone
Operating Temperature
Weather Proof Standard
Weight
Dimensions
Regulatory
Power Source
Power Consumption

Specification

20 users
Supports
Tripwire, Intrusion, Abandoned/Missing, Face Detection
iPhone, iPad, Android Phone
-30°C ~ 65°C / Less than 90% RH
IP66
8.5Kg
Φ375(mm)×246(mm)×210(mm)
CE, FCC, RoHS and EN50155
DC 12V/5A
30, 60W (IR on)