

**CP- UNR-404T2-MW2****4 Channel PoE Mobile Standalone NVR****Main Features**

- Up to 4 channel 1080P cameras Realtime live view
- H.264/ H.265/MJPEG dual codec decoding
- Max 200 Mbps recording rate
- Built-in module (GPS/3G/ Dual 4G/ Wi-Fi optional)
- 4 PoE Ports
- Support 2 SATA HDDs,1 SD Card, 3 USB Port
- Aviation connectors adopted
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



# CP- UNR-404T2-MW2

## 4 Channel PoE Mobile Standalone NVR



### Feature

Processor  
 IP Camera Input  
 Operating System  
 Two-way Talk  
 Video Input  
 Video Output  
 Compression  
 Video Resolution  
 Video Recording  
 Video Display Split  
 Privacy Masking  
 Motion Detection  
 Video Loss  
 Camera Blank  
 Alarm Input  
 Alarm Output  
 Smart Phone  
 Hard Disk  
 SD Card  
 Trigger Events  
 Recording Mode  
 Search Mode  
 Playback  
 Backup Mode  
 Interface Ports  
 Max User Account  
 Record Interval  
 Wi-Fi  
 GPS  
 Ethernet

### Specification

Dual-core embedded processor  
 4 channel  
 Embedded Linux  
 1ch Mic in, 1ch Mic out  
 4Ch.  
 1 HDMI, 1 VGA, 2 TV  
 H.264/H.265/G.711/PCM  
 1920×1080, 1280×1024, 1280×720, 1024×768  
 Max 200 Mbps  
 1/4  
 4 rectangular zones (each camera)  
 Zones: 396(22×18)  
 Supports  
 Supports  
 8 channel  
 3 channel  
 iPhone, iPad, Android, Windows Phone  
 2 SATA ports  
 1 SD card  
 Recording, PTZ, Tour, Alarm out, Email, FTP, Snapshot, Buzzer & Screen tips  
 Manual, Schedule (Regular (Continuous), MD, Alarm), Stop  
 Time/Date, Alarm, MD & Exact search (accurate to second), Smart search  
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom  
 USB Device/eSATA Device/Network/ External HDD  
 3 USB Port, 1 RS232, 1 RJ45, 1 RS485, 1 eSATA, G-sensor  
 128 users  
 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec  
 Built-in 3G / Dual 4G / Wi-Fi module (optional)  
 Built-in high accurate GPS module (optional)  
 1RJ-45 port (10/100/1000M)



**CP- UNR-404T2-MW2****4 Channel PoE Mobile Standalone NVR****Feature**

Protocols  
Power Supply  
Power Consumption  
Working Temp  
Anti Vibration  
Casing  
Regulatory  
Dimensions  
Weight

**Specification**

TCP/IP, UDP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Email, Alarm Server  
6V~36V  
≤15W  
-30°C (heater optional)~+60°C / 10%~95%RH / 86~106kpa  
As Per EN50155 standard for various Mobile Vehicle and Railway applications  
Aluminium Alloy  
CE, FCC, RoHS and EN50155  
180mm × 208mm × 100mm  
3 KG (Without HDD)