

**CP- UNR-408T2-MW2****8 Channel PoE Mobile Standalone DVR****Main Features**

- Up to 8 channel 1080P cameras realtime live view
- H.264/ H.265/MJPEG dual codec decoding
- Max 200 Mbps recording rate
- Built-in module (GPS/3G/ Dual 4G/ Wi-Fi optional)
- 8 PoE Ports
- Support 2 SATA HDDs,1 SD Card, 3 USB Port
- Aviation connectors adopted
- HDMI/VGA/TV simultaneous video output
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



# CP- UNR-408T2-MW2

## 8 Channel PoE Mobile Standalone DVR



### Feature

Processor  
IP Camera Input  
Operating System  
Two-way Talk  
Video Input  
Video Output  
Compression  
Video Resolution  
Video Recording  
Video Display Split  
Privacy Masking  
Motion Detection  
Video Loss  
Camera Blank  
Alarm Input  
Alarm Output  
Smart Phone  
Hard Disk  
SD Card  
Trigger Events  
Recording Mode  
Search Mode  
  
Playback  
  
Backup Mode  
Interface Ports  
Max User Account  
Record Interval  
Wi-Fi  
GPS  
Ethernet

### Specification

Dual-core embedded processor  
8 channel  
Embedded Linux  
1ch Mic in, 1ch Mic out  
8Ch.  
1 HDMI, 1 VGA, 2 TV  
H.264/H.265/G.711/PCM  
1920×1080, 1280×1024, 1280×720, 1024×768  
Max 200 Mbps  
1/4/8/9  
4 rectangular zones (each camera)  
Zones: 396(22×18)  
Supports  
Supports  
8 channel  
2 channel  
iPhone, iPad, Android, Windows Phone  
2 SATA ports  
1 SD card  
Recording, PTZ, Tour, Alarm out, Email, FTP, Snapshot, Buzzer & Screen tips  
Manual, Schedule (Regular (Continuous), MD, Alarm), Stop  
Time/Date, Alarm, MD & Exact search (accurate to second), Smart search  
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom  
USB Device/eSATA Device/Network/ External HDD  
3 USB Port, 1 RS232, 1 RJ45, 1 RS485, 1 eSATA, G-sensor  
128 users  
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec  
Built-in 3G / Dual 4G/ Wi-Fi module (optional)  
Built-in high accurate GPS module (optional)  
1RJ-45 port (10/100M)



# CP- UNR-408T2-MW2

## 8 Channel PoE Mobile Standalone DVR



### Feature

Protocols

Power Supply

Power Consumption

Working Temp

Anti Vibration

Casing

Regulatory

Dimensions

Weight

### Specification

TCP/IP, UDP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Email, Alarm Server

6V~36V

≤15W

-10°C ~+60°C / 10%~95%RH / 86~106kpa

As Per EN50155 standard for various Mobile Vehicle and Railway applications

Aluminium Alloy

CE, FCC, RoHS and EN50155

180mm × 208mm × 100mm

3 KG (Without HDD)

