

CP- VNR-3116-8P**16 Ch. 4K 8PoE Network Video Recorder****INDIGO****Main Features**

- 16 Channel IP Camera Input
- H.265/H.264 dual Video Formats
- Support 4K Resolution Upto 8MP Recording
- 60Mbps Incoming/ 80Mbps Outgoing Bandwidth
- Support 1 SATA HDDs up to 8TB, 3 USB Ports, 8 PoE Ports
- Support Multi-brand network cameras
- Mobile Software: Android, iOS
- CMS Software: IVMS



CP- VNR-3116-8P

16 Ch. 4K 8PoE Network Video Recorder



Feature

Processor

IP Camera Input

Operating System

Two-way Talk

User Interface

Video Output

Compression

Video Resolution

Video Recording

Video Display Split

Audio Input

Audio Output

Alarm Input

Alarm Output

Hard Disk

Playback

Interface Ports

Max User Account

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Working Humidity

Dimensions

Weight

Specification

Dual-core embedded processor

16 channel

Embedded LINUX

1 channel, RCA

GUI

HDMI, VGA , 4K(3840 x 2160)@30Hz, 1920 x 1080P@60Hz, 1920 x 1080P@50Hz, 1600 x 1200@60Hz, 1280 x 1024@60Hz, 1280 x 720@60Hz, 1024 x 768@60Hz

H.265 / H.264

Upto 8MP, 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF

60Mbps

1/4/8/9/16

1 channel, RCA

1 channel, RCA

4 channel

1 channel

1 SATA ports, up to 8TB

16 Channel

3 USB Port, 1 RJ45

128

1 RJ-45 10M/100M Self-adaptive Ethernet Interface, 8 independent 100 Mbps PoE Network

HTTP, TCP/IP, IPV4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, IP Server, P2P, ONVIF

52V DC , PoE: IEEE 802.3at, IEEE 802.3af

≤ 5 W , PoE: Max 30W for single port , Max 108W in total (13.5W for each)

-10°C ~ + 55°C (+14°F ~ +131°F)

10% ~ 90%

44mm × 260mm × 240mm (1.7" × 10.2" × 9.4")

≤ 1.12 Kg

