

CP- VNR-3208**8 Ch. 4K Network Video Recorder****INDIGO****Main Features**

- 8 Channel IP Camera Input
- H.265/H.264 dual Video Formats
- Support 4K Resolution Upto 8MP Recording
- 48 Mbps Incoming/Outgoing Bandwidth
- Support 2 SATA HDDs up to 16TB, 3 USB Ports
- Support Multi-brand network cameras
- Mobile Software: Android, iOS
- CMS Software: IVMS



CP- VNR-3208

8 Ch. 4K Network Video Recorder



Feature

Processor
Operating System
IP Camera Input
Two-way Talk
User Interface
Video Output
Compression
Video Resolution
Video Recording
Video Display Split
OSD
Bit Rate
Audio Input
Smart detection
Audio Output
Corridor Mode Screen
Alarm Input
Alarm Output
Hard Disk
ANR Technology
Fisheye De-warping Mode live and playback
Trigger Events
Cloud Upgrade
Search Mode
Playback
Backup Mode
Interface Ports
Max User Account

Specification

Dual-core embedded processor
Embedded LINUX
8 channel
1 channel, RCA
GUI
HDMI, VGA , 4K(3840 x 2160)@30Hz, 1920 x 1080P@60Hz, 1920 x 1080P@50Hz, 1600 x 1200@60Hz, 1280 x 1024@60Hz, 1280 x 720@60Hz, 1024 x 768@60Hz
H.265 / H.264
8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
48Mbps
1/4/8/9
Camera Title, Time, Motion Detection, Recording
Supports
1 channel, RCA
Face Detection, Intrusion Detection, Cross Line Detection, Audio Detection, Defocus Detection, Scene Change Detection, Auto Tracking, Face Search, Behaviour Search, People Counting
1 channel, RCA
3/4/5/7/9/10/12/16/32
4 channel
1 channel
2 SATA ports, up to 16TB
Supports
Supports
Recording, PTZ, Alarm Out, Video Push, Email, Snapshot, Buzzer, etc
Supports
Time/Date, Alarm, MD, Exact Search (By Minute/Second)
1/4/9/16
USB, Network
3 USB Port, 1 RJ45
32

CP- VNR-3208**8 Ch. 4K Network Video Recorder****Feature**

Record Interval

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Working Humidity

Dimensions

Weight

Specification

1~256MB

1 RJ-45 10M/100M Self-adaptive Ethernet Interface

HTTP, TCP/IP, IPV4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, IP Server, P2P, ONVIF

12V DC

≤ 5 W

-10°C ~ + 55°C (+14°F ~ +131°F)

10% ~ 90%

46mm x 315mm x 380mm (1.8" x 12.4" x 15.0")

≤ 2.18 Kg