

CP- TNW-HP24G2F1-30**24 Ports PoE Switch****Main Features**

- Provide 24x 100Mbps downlink PoE Ethernet ports, 2x gigabit uplink Ethernet ports and 1x gigabit Fiber port
- Downlink Ethernet ports support PoE , each port supports max. 30W output
- Support power consumption indication(LED indicates power output status)
- Accord with IEEE802.3 , IEEE802.3u , IEEE802.3ab , IEEE802.3af/at standard
- 4K MAC address,2.75Mb cache

CP- TNW-HP24G2F1-30

24 Ports PoE Switch

Feature

Downlink Ports
Uplink Ports
Network Standard
Exchange Capacity
Transmission Distance
Data Package Cache
MAC Address List
PoE Power Supply
PoE Output
PoE Power Budget
CCTV Mode
Surge Immunity
ESD Protection
Power Input
Grounding Terminal
Operating Temperature
Storage Temperature
Humidity
Single Port Power Output
Dimensions
Color
Power Light

Specification

24x10/ 100Base- TX PoE+ , Link:16x Green LED PoE:16x Yellow LED
2x10/100/1000Base-T+1 x 1000Base-X(combo) , 2x Green LED
IEEE 802.3,IEEE 802.3u,IEEE 802.3 ab, IEEE 802.3z
8.8Gbps
100m(Max.)
2. 75Mb
4K
End- span(1/ 2, 3/ 6),IEEE802. 3 af/ at
270W , 5x LED (Including 3x Green, 1x Yellow, 1x Red), separately indicate 30%, 60% , 90%, 95%~100%
300W
Downlink ports only communicate with uplink ports , Restrain network storm under 2Mbps , Extend transmission distance to 250m , Rate:10Mbps(Downlink Ports)
6KV, Per: IEC61000- 4- 5
6KV/8KV, Per:IEC61000-4-2
1xAC Female Terminal , Mains on load,100~240VAC 50/ 60Hz
1xGrounding Terminal
-10°C~45°C
-40°C~+85°C
0~95%
Single Port PoE Power Output≤30W, Voltage 54VDC
442mm x 285mm x 44.5mm
Black
1x Red LED