

CP- UNR-404T2**4 Ch. Network Video Recorder****Main Features**

- 4 Ch. with 1080p Realtime Live View
- H.264+ and H.264 dual codec decoding
- Up to 5Mp resolution preview & playback
- Max 200Mbps incoming bandwidth
- Support 2 SATA HDDs up to 8TB, 2 USB
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



CP- UNR-404T2

4 Ch. Network Video Recorder



Feature

Processor
 Operating System
 IP Camera Input
 Two-way Talk
 User Interface
 Video Output
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Motion Detection
 Video Loss
 Camera Blank
 Alarm Input
 Alarm Output
 Hard Disk
 Smart Phone
 Trigger Events
 Recording Mode
 Search Mode
 Playback
 Backup Mode
 Max User Account
 Record Interval
 Interface Ports
 Ethernet
 Protocols
 Power Supply

Specification

Dual-core embedded processor
 Embedded LINUX
 4 channel
 1 channel Input, 1 channel Output, RCA
 GUI
 1 HDMI, 1 VGA
 H.264+/H.264/MJPEG
 1920 × 1080 , 1280 × 1024, 1280 × 720 , 1024 × 768
 Max 200 Mbps , 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P etc.
 1/4
 MD Zones: 396(22×18).
 Supports
 Supports
 4 Channel, Low Level Effective, Green Terminal Interface
 2 Channel, NO/NC Programmable, Green Terminal Interface
 2 SATA III Ports, up to 8TB
 iPhone, iPad, Android Phone
 Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen tips
 Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Camera Blank, Video Loss), Alarm, Stop
 Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
 USB Device / Network
 128 users
 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
 1 HDMI, 1 VGA, 2 USB(1 USB 2.0, 1 USB 3.0), 1 RS485, 1 RS232, 1 RJ45
 1 RJ-45 port (10/100M/1000M)
 HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.4
 DC12V/4A



 **CP- UNR-404T2****4 Ch. Network Video Recorder****Feature**

Power Consumption

Working Temp

Dimensions

Weight

Specification

<20W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

375mm x 285.8mm x 56mm

1.6kg (without HDD)