

**CP- UNR-408T2****8 Ch. Network Video Recorder****Main Features**

- 8 Ch. with 1080p Realtime Live View
- H.264+ and H.264 dual codec decoding
- Up to 5Mp resolution preview & playback
- Max 200Mbps incoming bandwidth
- Support 2 SATA HDDs up to 8TB, 2 USB
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



# CP- UNR-408T2

## 8 Ch. Network Video Recorder



### Feature

Processor  
IP Camera Input  
Operating System  
Two-way Talk  
User Interface  
Video Output  
Compression  
Video Resolution  
Video Recording  
Video Display Split  
Motion Detection  
Video Loss  
Camera Blank  
Alarm Input  
Alarm Output  
Hard Disk  
Smart Phone  
Trigger Events  
Recording Mode  
Search Mode  
Playback  
Backup Mode  
Interface Ports  
Record Interval  
Max User Account  
Ethernet  
Protocols  
Power Supply

### Specification

Dual-core embedded processor  
8 channel  
Embedded LINUX  
1 channel Input, 1 channel Output, RCA  
GUI  
1 HDMI, 1 VGA  
H.264+/H.264/MJPEG  
2560 × 1920, 2048 × 1536, 1920 × 1080, 1280 × 1024, 1280 × 720, 1024 × 768  
Max 200 Mbps, 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P etc.  
1/4/8/9  
MD Zones: 396(22×18).  
Supports  
Supports  
4 channel  
2 channel  
2 SATA III ports, up to 8TB  
iPhone, iPad, Android Phone  
Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen tips  
Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Camera Blank, Video Loss), Alarm, Stop  
Time/Date, Alarm, MD & Exact search (accurate to second), Smart search  
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom  
USB Device / Network  
1 HDMI, 1 VGA, 2 USB(1 USB 2.0, 1 USB 3.0), 1 RS485, 1 RS232, 1 RJ45  
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec  
128 users  
1 RJ-45 port (10/100M/1000M)  
HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.4  
DC12V/4A



 **CP- UNR-408T2****8 Ch. Network Video Recorder****Feature**

Power Consumption

Working Temp

Dimensions

Weight

**Specification**

20W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

375mm x 327mm x 53mm

2.6kg (without HDD)