

CP- SMR-N411-PGW**4 Ch. H.264 Mobile NVR****Main Features**

- 4 channels 1080P channel IPC
- Built-in 4G/3G for live view
- H.264 video compression
- Supports SD card for mirror recording
- Supports Hard disk for main recording
- Supports GPS for location tracking
- Support Wi-Fi
- Vibration-resistant design to meet various environment needs



CP- SMR-N411-PGW**4 Ch. H.264 Mobile NVR****Feature**

Operating System

Operation Interface

Control Mode

Video Compression

Video Systems

Total Resource

Resolution

Audio Compression

Video Input

Video Output

Recording Mode

Audio Input

Audio Output

Audio Signal Standard

Pre-recording

Display Split

Post-recording

Mirror/Dual Recording

OSD

Playback

Image Quality

GPS

Search Mode

Sensors

Backup Mode

USB

Hard Disk

MIC

Ethernet

4G/3G Support

Wi-Fi

Serial Ports

Specification

Embedded Linux 3.0.8

Semi-transparent GUI

Network, mouse, Integrated Monitor

H.264

NTSC/PAL

4 x 1080P@30FPS (IPC)

Digital: 1080P(1920X1080), 720P(1280X720)

ADPCM

4 channels 1080P IPC

1 channel

Boot up/Manual/Schedule/Alarm

4 channels (4 channels IPC audio input)

1 channel

Electrical level: 2Vpp Input impedance: 4.7kΩ

0-60 minutes

1/4

0-30 minutes

Supports

GPS Location, Alarm, Vehicle No, Speed, Date/Time

1 channel by local playback

1-8 levels adjustable (1 is the best)

Location tracking, Speed detection and Time sync

Date/time, channel, event

8 Inputs, 2 Outputs

USB, HDD, Network

1 x USB2.0(Type A) + 1 x USB2.0(Type B)

Supports 2.5" SATA hard disk x 1

One MIC interface

Ethernet- RJ45 x 1 (10/100 M), IPC Ethernet- 4 x RJ45 (10/100 M POE port)

EVDO/WCDMA/TDD-LTE/FDD-LTE

802.11b/g/n

RS232 x 2, RS485 x 2

CP- SMR-N411-PGW**4 Ch. H.264 Mobile NVR****Feature**

Control panel
Power Input
Interface Ports
Power Output
Power Consumption
Standby Power Consumption
Dimension (W×H×D)
Weight
Operating Temperature
Relatively Operating Humidity

Specification

Integrated Monitor
DC8-36V, ACC
SD card slot x 1, 1 SIM slot, 1 channel pulse speed detection
5V@1A & 12V@1A
40W
≈0W
255.3mm x 150mm x 89.1mm
2.2 KG
-10°C ~ +70°C or -40°C ~ +70°C(with heater)
8%-90% (No Condense)