



**CP-UNC-DD13L3****1.3 MP HD IR Dome Camera - 30Mtr.****Main Features**

- 1/3" 1.3Megapixel PS CMOS Image Sensor
- Max 25/30fps@1.3MP
- H.264 and MJPEG dual-stream encoding
- DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- Smart Detection supported
- 3.6mm fixed lens (2.8mm, 6mm optional)
- IR Range of 30 Mtrs, IP67, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



# CP- UNC-DD13L3

## 1.3 MP HD IR Dome Camera - 30Mtr.

### Feature

Image Sensor  
 Minimum Illumination  
 Shutter Speed  
 White Balance  
 Gain Control(AGC)  
 Lens  
 Back Light Compensation  
 S/N Ratio  
 Video Streaming  
 Resolution  
 Privacy Mask  
 ICR  
 Protocol  
 Smart Detection  
 Ethernet  
 User Account  
 IR  
 Smart Phone  
 Operating Temperature  
 Power Source  
 Power Consumption  
 Weatherproof Standard  
 Dimension  
 Weight

### Specification

1/3" 1.3Megapixel progressive scan CMOS  
 0.01Lux/F2.0(Color), 0Lux/F2.0(IR on)  
 Auto/Manual, 1/3(4)~1/10000s  
 Auto/Manual  
 Auto/Manual  
 3.6mm(2.8mm, 6mm optional)  
 BLC / HLC / DWDR  
 More than 50dB  
 Main Stream: 1.3M/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps), Third Stream: 720P(1~13/4fps)  
 1.3M(1280x960)/720P(1280x 720)/ D1(704x 576/704x 480) /CIF(352x 288/352x 240)  
 Up to 4 areas  
 Auto(ICR)/Color/B/W  
 IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS,Bonjour, ONVIF, PSIA, CGI  
 Tripwire, Intrusion, Scene Change, Face detect  
 RJ-45 (10/100Base-T)  
 20 Users  
 IR Range of 30 Mtr.  
 iPhone, iPad, Android, Windows Phone  
 -40°C~+60°C, Less than 95% RH  
 DC12V, PoE (802.3af)  
 Max 5W  
 IP67  
 Ø93.4mm × 80mm  
 0.3Kg(0.42Kg with packaging)