

**CP- UNC-TE30FL3-M****3 MP Full HD IR Bullet Camera - 30Mtr.****Main Features**

- 1/3" 3MP PS CMOS Image Sensor
- Max 20fps@3M and 25/30fps@1080P
- H.264 and MJPEG dual-stream encoding
- DWDR, Day/Night(ICR), Auto Iris, 3DNR, AWB, AGC, BLC
- 2.7 -12mm Varifocal Lens
- IR Range of 30 Mtrs, Micro SD, IP66, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



# CP- UNC-TE30FL3-M

## 3 MP Full HD IR Bullet Camera - 30Mtr.

### Feature

Image Sensor  
 Minimum Illumination  
 Shutter Speed  
 White Balance  
 Lens  
 Gain Control(AGC)  
 Back Light Compensation  
 S/N Ratio  
 Video Compression  
 Video Streaming  
 Resolution  
 Privacy Mask  
 ICR  
 Audio Input  
 Audio Output  
 Audio Compression  
 Alarm IN  
 Alarm Out

### Specification

1/3" 3MP Progressive scan CMOS  
 Color: 0. 1Lux/F1.2, 0Lux/F1.2(IR on)  
 Auto/Manual, 1/3(4)~1/10000s  
 Auto/Manual  
 2.7 -12mm Lens  
 Auto/Manual  
 BLC/ HLC/ DWDR  
 More than 50dB  
 H.264/MJPEG  
 Main Stream: 3M(1~20fps)/1080P/720P(1~25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)  
 3M(2048× 1536)/1080P(1920× 1080) / 720P(1280× 720) /D1(704× 576) /CIF(352× 288)  
 Up to 4 areas  
 Auto(ICR)/Color/B/W  
 1 Channel  
 1 Channel  
 G.711a / G.711u/ PCM  
 2 Channel  
 1 Channel

### Protocol

IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS,Bonjour, ONVIF, PSIA, CGI

### Ethernet

RJ-45 (10/100Base-T)

### User Account

20 Users

### Smart Phone

iPhone, iPad, Android, Windows Phone

### IR

IR Range of 30 Mtr.

### Micro SD

Micro SD, Max 64GB

### Operating Temperature

-20°C~+60°C , Less than 90%RH

### Power Source

DC12V(AC 24V optional), PoE(802.3af)

### Power Consumption

Max 7W

### Weatherproof Standard

IP66

### Dimension

Φ104mm× 306.7mm

### Weight

1.25Kg.