

# CP- UNR-404T1-P4

## 4 Ch. Network Video Recorder with 4 PoE Ports



### Main Features

- 4 Ch. with 1080p Realtime Live View
- H.264/MJPEG dual codec decoding
- Up to 5Mp resolution preview&playback
- Max 80Mbps incoming bandwidth
- Support 1 SATA HDDs up to 4TB, 2 USB2.0
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.3 conformance, 4 Ports PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



# CP- UNR-404T1-P4

## 4 Ch. Network Video Recorder with 4 PoE Ports

### Feature

Processor  
 Operating System  
 IP Camera Input  
 Two-way Talk  
 User Interface  
 Video Output  
 Compression  
 Video Resolution  
 Video Recording  
 Video Display Split  
 Motion Detection  
 Video Loss  
 Camera Blank  
 Smart Phone  
 Hard Disk  
 Trigger Events  
 Recording Mode  
 Search Mode  
 Playback  
 Backup Mode  
 Interface Ports  
 Record Interval  
 Max User Account  
 Ethernet  
 Protocols  
 Power Supply  
 Power Consumption  
 Working Temp  
 Dimensions  
 Weight

### Specification

Dual-core embedded processor  
 Embedded LINUX  
 4 channel  
 1 channel Input, 1 channel Output, RCA  
 GUI  
 1 HDMI, 1 VGA  
 H.264 / MJPEG  
 2560×1920, 2048×1536, 1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768  
 Max 80 Mbps  
 1/4  
 MD Zones: 396(22×18).  
 Supports  
 Supports  
 iPhone, iPad, Android, Windows Phone  
 1 SATA ports, up to 8TB  
 Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen  
 Manual, Schedule(Regular(Continuous), MD, Alarm), Stop  
 Time/Date, Alarm, MD & Exact search (accurate to second), Smart search  
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom  
 USB Device / Internal SATA burner/ Network  
 1 HDMI, 1 VGA, 2 USB2.0, 1 RJ45  
 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec  
 128 users  
 1 RJ-45 port (10/100M/1000M)  
 HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.3  
 DC12V/2A  
 NVR: 10W(without HDD), PoE: Max 25.5W for single port  
 -10 ~+55°C / 10~90%RH / 86~106kpa  
 325mm × 240mm × 45mm  
 1.25 Kg (without HDD)