

**CP- UNR-404T2N****4 Ch. Network Video Recorder****Main Features**

- 4 Ch. with 1080p Realtime Live View
- H.264/MJPEG dual codec decoding
- Up to 5Mp resolution preview&playback
- Max 200Mbps incoming bandwidth
- Support 2 SATA HDDs up to 8TB, 2 USB2.0
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



# CP-UNR-404T2N

## 4 Ch. Network Video Recorder

### Feature

Processor  
 IP Camera Input  
 Operating System  
 Two-way Talk  
 User Interface  
 Video Output  
 Compression  
 Video Resolution  
 Video Recording  
 Video Display Split  
 Motion Detection  
 Video Loss  
 Camera Blank  
 Hard Disk  
 Smart Phone  
 Trigger Events  
 Recording Mode  
 Search Mode  
  
 Playback  
  
 Backup Mode  
 Interface Ports  
 Max User Account  
 Record Interval  
 Ethernet  
 Protocols  
 Power Supply  
 Power Consumption  
 Working Temp  
 Dimensions

### Specification

Dual-core embedded processor  
 4 channel  
 Embedded LINUX  
 1 channel Input, 1 channel Output, RCA  
 GUI  
 1 HDMI, 1 VGA  
 H.264 / MJPEG  
 2560 × 1920, 2048 × 1536, 1920 × 1080, 1280 × 1024, 1280 × 720, 1024 × 768  
 Max 200 Mbps  
 1/4  
 MD Zones: 396(22×18).  
 Supports  
 Supports  
 2 SATA ports, up to 8TB, Raid (Redundancy)  
 iPhone, iPad, Android, Windows Phone  
 Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen  
 Manual, Schedule(Regular(Continuous), MD, Alarm), Stop  
 Time/Date, Alarm, MD & Exact search (accurate to second), Smart search  
  
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom  
  
 USB Device / Internal SATA burner/ Network  
 1 HDMI, 1 VGA, 2 USB2.0, 1 RS485, 1 RS232, 1 RJ45  
 128 users  
 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec  
 1 RJ-45 port (10/100M/1000M)  
 HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.3  
 DC12V/4A  
 20W(without HDD)  
 -10 ~+55°C / 10~90%RH / 86~106kpa  
 375mm×285mm×50mm

 **CP- UNR-404T2N****4 Ch. Network Video Recorder****Feature**

Weight

**Specification**

2 Kg (without HDD)