


CP- UVR-0404G8D-H**4 Ch. 720P HDCVI DVR****CP PLUS**
CORAL**Main Features**

- Up to 4 cameras with 1080p Realtime Preview
- Support HDCVI / Analog / IP Video input
- H.264 dual-stream Video Compression
- HDMI / VGA / TV Simultaneous Video Output
- Support 8 SATA ports(8HDDs or 6HDDs 1CD/DVD-RW), up to 32TB, 1 eSATA up to 16TB, 4 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software:KVMS, KVMS Pro



CP- UVR-0404G8D-H

4 Ch. 720P HDCVI DVR



Feature

Processor
 Operating System
 Two-way Talk
 User Interface
 Video Input
 Video Output
 Video Standard
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Privacy Masking
 Audio Input
 Audio Output
 Motion Detection
 Video Loss
 Camera Blank
 Alarm Input
 Alarm Output
 Hard Disk
 Smart Phone
 Trigger Events
 Recording Mode
 Search Mode

 Playback

 Backup Mode
 Record Interval
 Max User Account

Specification

Embedded processor
 Embedded LINUX
 1 channel Input, 1 channel Output, BNC
 GUI
 4 channel, BNC
 1 HDMI, 1 VGA, 1 TV
 HDCVI: 1080P/720P HDCVI Camera, Analog: NTSC(525Line, 60f/s), PAL(625Line, 50f/s), IP: 1080P/720P/D1/CIF IP Camera
 H.264 / G.711
 1920×1080, 1280×1024, 1280×720, 1024×768
 Main Stream: 1080P(1~12/15fps)/720P/960H/D1/HD1/2CIF/CIF(1~25/30fps), Extra Stream: CIF/QCIF(1~25/30fps)
 1/4
 4 rectangular zones (each camera)
 4 channel, RCA
 1 channel, RCA
 Supports
 Supports
 Supports
 4 Channel
 6 Channel
 8 SATA ports(8HDDs or 6HDDs+1CD/DVD-RW), up to 32TB, 1 eSATA port, up to 16TB
 iPhone, iPad, Android, Windows Phone
 Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips
 Manual, Schedule(Regular(Continuous), MD), Stop
 Time/Date, MD & Exact search (accurate to second)

 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom

 USB Device / Network
 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
 128 users

CP- UVR-0404G8D-H

4 Ch. 720P HDCVI DVR



Feature

Interface Ports

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

1 HDMI, 1 VGA, 1 RS485, 1 RS422, 1 RS232, 4 USB2.0

2 RJ-45 port (10/100M/1000M)

HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P

AC 100~240 V, 50/60 Hz

40W (Without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

440mm× 460mm× 68mm

6.5 Kg(without HDD)