

CP- UVR-0404K4**4 Ch. 720P-Advanced HDCVI DVR****CP PLUS**
CORAL**Main Features**

- Support HDCVI/Analog/IP Video input
- All channel 720P Realtime or 1080P non-Realtime Recording
- H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support Multi-brand network cameras
- Support 4 SATA HDD up to 16TB, 1 eSATA, 3 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



CP- UVR-0404K4

4 Ch. 720P-Advanced HDCVI DVR



Feature

Processor
 Operating System
 Two-way Talk
 User Interface
 Video Input
 Video Output
 Video Standard
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Privacy Masking
 Audio Input
 Audio Output
 Motion Detection
 Video Loss
 Camera Blank
 Alarm Input
 Alarm Output
 Hard Disk
 Smart Phone
 Trigger Events
 Recording Mode
 Search Mode
 Playback
 Backup Mode
 Record Interval
 Interface Ports

Specification

Embedded processor
 Embedded LINUX
 1 channel Input, 1 channel Output, BNC
 GUI
 4 channel, BNC
 1 HDMI, 1 VGA, 1TV
 Analog: NTSC(525Line, 60f/s), PAL(625Line, 50f/s), HDCVI: 1080P/720P HDCVI Camera, IP: 1080P/720P/D1/CIF IP Camera
 H.264 / G.711
 1080P(1920×1080) / 720P(1280×720) / 960H(960×576/960×480) / D1/4CIF (704×576/704×480) / CIF(352×288/352×240) / QCIF(176×144/176×120)
 Main Stream: 1080P(1~12/15fps) / 720P/960H / D1(1~25/30fps), Extra Stream: CIF / QCIF
 1/4
 4 rectangular zones (each camera)
 4 channel, RCA
 1 channel, RCA
 Supports
 Supports
 Supports
 4 channel
 6 channel
 4 SATA ports(4 HDDs or 3HDDs+1 CD/DVD-RW), up to 16TB, 1 eSATA port (Max 4 SATA
 iPhone, iPad, Android, Windows Phone
 Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips
 Manual, Schedule(Regular(Continuous), MD), Stop
 Time/Date, MD & Exact search (accurate to second)
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom
 USB Device/Internal SATA burner/Network
 1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
 1 HDMI, 1 VGA, 3 USB2.0, 1 RS485, 1RS232

CP- UVR-0404K4**4 Ch. 720P-Advanced HDCVI DVR****Feature**

Max User Account

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

128 users

RJ-45 port (10/100M/1000M)

HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P, ONVIF Version 2.4 conformance

AC 100~240 V, 50/60 Hz

40W(Without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

440mm × 416mm × 68mm

6KG(without HDD)