

**CP- UVR-0801L1-4KH****8 Ch. 4K H.265 Cosmic HD DVR****Main Features**

- Auto Adaptive HDCVI/AHD/TVI/CVBS/IP signals
- Support upto 8MP IP Camera
- Max 48Mbps Incoming Bandwidth
- H.265+ /H.265 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 1 SATA HDD up to 10TB, 2 USB Ports
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



# CP- UVR-0801L1-4KH

## 8 Ch. 4K H.265 Cosmic HD DVR



### Feature

Processor  
Operating System  
IP Camera Input  
Two-way Talk  
User Interface  
Video Input  
Video Output  
Video Standard  
Compression  
Video Resolution  
Video Recording  
Video Display Split  
OSD  
Audio Input  
Audio Output  
Motion Detection  
Video Loss  
Camera Blank  
Audio Compression  
Hard Disk  
Audio Sample Rate  
Smart Phone  
Audio Bit Rate  
Trigger Events  
Recording Mode  
Search Mode  
Playback

### Specification

Embedded processor  
Embedded LINUX  
8+4 Ch. : each channel up to 8MP  
Reuse audio in/out, RCA  
GUI  
8 channel, BNC  
1 HDMI, 1 VGA  
Analog: NTSC(525Line, 60f/s), PAL(625Line, 50f/s)  
H.265+/H.265/H.264+/H.264  
HDMI: 3840×2160, 2560×1440, 1920×1080, 1280×1024, 1280×720, VGA: 1920×1080, 1280×1024, 1280×720  
Main stream: 4K(1~7fps); 6MP(1~10fps); 5MP(1~12fps); 4MP/3MP(1~15fps); 4M-N/1080P/720P/960H/D1/CIF(1~25/30fps), Sub stream: 960H(1~15fps); D1/CIF(1~25/30fps)  
1/4/8/9  
Camera title, Time, Video loss, Camera lock, Motion detection, Recording  
1 channel, RCA  
1 channel, RCA  
MD Zones: 396 (22 × 18)  
Supports  
Supports  
AAC (only for the 1st channel), G.711A, G.711U, PCM  
1 SATA port, up to 10TB  
8KHz, 16 bit Per Channel  
iPhone, iPad, Android Phone  
64Kbps Per Channel  
Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips  
Manual, Schedule (General, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop  
Time /Date, Alarm, MD and Exact Search (accurate to second)  
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom



**CP- UVR-0801L1-4KH****8 Ch. 4K H.265 Cosmic HD DVR****Feature**

Backup Mode  
Interface Ports  
Max User Account  
Record Interval  
Ethernet  
  
Protocols  
  
Power Supply  
Power Consumption  
Working Temp  
Dimensions  
Weight

**Specification**

USB Device/ Network  
1 HDMI, 1 VGA, 2 USB Ports(1 USB 2.0, 1 USB 3.0), 1 RS485  
128 users  
1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec  
1 RJ-45 port (1000M)  
  
HTTP, HTTPS, TCP/IP, IPv4/IPv6, Wi-Fi, 3G/4G, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, IP Search, ONVIF 16.12, CGI Conformant  
  
DC12V/2A  
<10W(without HDD)  
-10 ~+55°C / 10~90%RH  
260mm×236mm×48mm  
0.9kg (without HDD)