

**CP- UVR-0801L2-4KH****8 Ch. 4K H.265 Cosmic HD DVR****Main Features**

- Auto Adaptive HDCVI/AHD/TVI/CVBS/IP signals
- Support upto 8MP IP Camera
- Max 48Mbps Incoming Bandwidth
- H.265+ /H.265 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 2 SATA HDD up to 10TB Each, 2 USB Ports
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



# CP- UVR-0801L2-4KH

## 8 Ch. 4K H.265 Cosmic HD DVR



### Feature

Processor  
 Operating System  
 IP Camera Input  
 Two-way Talk  
 User Interface  
 Video Input  
 Video Output  
 Video Standard  
 Compression  
 Video Resolution  
 Video Recording  
 Video Display Split  
 OSD  
 Audio Input  
 Audio Output  
 Motion Detection  
 Video Loss  
 Camera Blank  
 Audio Compression  
 Hard Disk  
 Audio Sample Rate  
 Smart Phone  
 Audio Bit Rate  
 Trigger Events  
 Recording Mode  
 Search Mode  
 Playback

### Specification

Embedded processor  
 Embedded LINUX  
 8+4 Ch. : each channel up to 8MP  
 Reuse audio in/out, RCA  
 GUI  
 8 channel, BNC  
 1 HDMI, 1 VGA  
 Analog: NTSC(525Line, 60f/s), PAL(625Line, 50f/s)  
 H.265+/H.265/H.264+/H.264  
 HDMI: 3840×2160, 2560×1440, 1920×1080, 1280×1024, 1280×720, VGA: 1920×1080, 1280×1024, 1280×720  
 Main stream: 4K(1~7fps); 6MP(1~10fps); 5MP(1~12fps); 4MP/3MP(1~15fps); 4M-N/1080P/720P/960H/D1/CIF(1~25/30fps), Sub stream: 960H(1~15fps); D1/CIF(1~25/30fps)  
 1/4/8/9  
 Camera title, Time, Video loss, Camera lock, Motion detection, Recording  
 1 channel, RCA  
 1 channel, RCA  
 MD Zones: 396 (22 × 18)  
 Supports  
 Supports  
 AAC (only for the 1st channel), G.711A, G.711U, PCM  
 2 SATA port, up to 10TB Each  
 8KHz, 16 bit Per Channel  
 iPhone, iPad, Android Phone  
 64Kbps Per Channel  
 Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips  
 Manual, Schedule (General, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop  
 Time /Date, Alarm, MD and Exact Search (accurate to second)  
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom



**CP- UVR-0801L2-4KH****8 Ch. 4K H.265 Cosmic HD DVR****Feature**

Backup Mode  
Interface Ports  
Max User Account  
Record Interval  
Ethernet  
Protocols  
Power Supply  
Power Consumption  
Working Temp  
Dimensions  
Weight

**Specification**

USB Device/ Network  
1 HDMI, 1 VGA, 2 USB Ports(1 USB 2.0, 1 USB 3.0), 1 RS485  
128 users  
1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec  
1 RJ-45 port (1000M)  
HTTP, HTTPS, TCP/IP, IPv4/IPv6, Wi-Fi, 3G/4G, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, IP Search, ONVIF 16.12, CGI Conformant  
DC12V/4A  
<10W(without HDD)  
-10 ~+55°C / 10~90%RH  
375mm×287mm×53mm  
1.5kg (without HDD)