

CP- UVR-1616G8D-H

16 Ch. Tribrid HDCVI DVR

CP PLUS
CORAL



Main Features

- Up to 16 cameras with 720p Realtime / 1080p non Realtime Preview
- Support HDCVI / Analog / IP Video input
- H.264 dual-stream Video Compression
- HDMI / VGA / TV Simultaneous Video Output
- Support 8 SATA HDDs up to 32TB, 1 eSATA up to 16TB, 4 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software:KVMS, KVMS Pro



CP- UVR-1616G8D-H

16 Ch. Tribrid HDCVI DVR



Feature

Processor
 Operating System
 Two-way Talk
 User Interface
 Video Input
 Video Output
 Video Standard
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Privacy Masking
 Audio Input
 Audio Output
 Motion Detection
 Video Loss
 Camera Blank
 Alarm Input
 Alarm Output
 Smart Phone
 Hard Disk
 Trigger Events
 Recording Mode
 Search Mode
 Playback
 Backup Mode
 Interface Ports
 Max User Account

Specification

Embedded processor
 Embedded LINUX
 1 channel Input, 1 channel Output, BNC
 GUI
 16 channel, BNC
 1 HDMI, 1 VGA, 1 BNC
 HDCVI: 1080P/720P HDCVI Camera, Analog: NTSC(525Line, 60f/s), PAL(625Line, 50f/s), IP: 1080P/720P/D1/CIF IP Camera
 H.264 / G.711
 1920×1080, 1280×1024, 1280×720, 1024×768
 Main Stream: 1080P(1~12/15fps)/720P/960H/D1/HD1/2CIF/CIF(1~25/30fps), Extra Stream: CIF/QCIF(1~25/30fps)
 1/4/8/9/16
 4 rectangular zones (each camera)
 16 channel, RCA
 1 channel, RCA
 Supports
 Supports
 Supports
 16 Channel
 6 Channel
 iPhone, iPad, Android, Windows Phone
 8 SATA ports(8HDDs or 6HDDs+1CD/DVD-RW), up to 32TB, 1 eSATA port, up to 16TB
 Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips
 Manual, Schedule(Regular(Continuous), MD), Stop
 Time/Date, MD & Exact search (accurate to second)
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom
 USB Device/eSATA Device/Internal SATA burner/Network
 1 HDMI, 1 VGA, 1 RS485, 1 RS422, 1 RS232, 4 USB2.0
 128 users

CP- UVR-1616G8D-H

16 Ch. Tribrid HDCVI DVR



Feature

Record Interval

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

RJ-45 port (10/100M/1000M)

HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P

AC 100~240 V, 50/60 Hz

40W (Without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

440mm× 460mm× 89mm

6.5KG(without HDD)