

CP- UVR-2401E2

24 Ch. 720P HDCVI DVR



Main Features

- Support HDCVI/Analog/IP Video input
- All channel 720P Realtime Recording
- H.264 dual-stream Video Compression
- HDMI / VGA / TV Simultaneous Video Output
- Support Multi-brand network cameras
- Support 2 SATA HDDs up to 8TB, 2 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software:KVMS, KVMS Pro



CP- UVR-2401E2

24 Ch. 720P HDCVI DVR

Feature

Processor
 Operating System
 Two-way Talk
 User Interface
 Video Input
 Video Output
 Video Standard
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Privacy Masking
 Audio Input
 Audio Output
 Motion Detection
 Video Loss
 Camera Blank
 Hard Disk
 Smart Phone
 Trigger Events
 Recording Mode
 Search Mode

 Playback

 Backup Mode
 Record Interval
 Max User Account
 Interface Ports
 Ethernet

Specification

Embedded processor
 Embedded LINUX
 Reuse audio input/output channel 1
 GUI
 24 channel, BNC
 1 HDMI, 1 VGA, 1 TV
 Analog: NTSC / PAL, HDCVI: 720P HDCVI Camera, IP: 1080P/720P/D1/CIF IP Camera
 H.264 / G.711
 1920×1080, 1280×1024, 1280×720, 1024×768
 Main Stream: 720P/960H / D1(1~25/30fps), Extra Stream: CIF / QCIF(1~25/30fps)
 1/4/8/9/16/25
 4 rectangular zones (each camera)
 1 channel, RCA
 1 channel, RCA
 Supports
 Supports
 Supports
 2 SATA ports, up to 8TB
 iPhone, iPad, Android, Windows Phone
 Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips
 Manual, Schedule(Regular(Continuous), MD), Stop
 Time/Date, MD & Exact search (accurate to second)

 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom

 USB Device/Internal SATA burner/Network
 1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
 128 users
 1 HDMI, 1 VGA, 2 USB2.0, 1 RS485
 RJ-45 port (10/100M/1000M)



CP- UVR-2401E2
24 Ch. 720P HDCVI DVR

Feature

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P, ONVIF Version 2.4 conformance

DC12V/5A

15W(Without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

375mm × 285mm × 55mm

2.35Kg(without HDD)