

**CP- VNR-3108LB-8P****8 Ch. 8PoE Network Video Recorder****INDIGO****Main Features**

- 8 Channel IP Camera Input
- Support Ultra 265/H.265/H.264 video formats
- Support HDMI and VGA simultaneous output
- 40Mbps Incoming/ 40Mbps Outgoing Bandwidth
- Support Up to 2MP Resolution Recording
- Support 1 SATA HDDs up to 8TB, 2 USB Ports, 8 PoE Ports
- Support Multi-brand network cameras
- Mobile Software: Android, iOS
- CMS Software: IVMS



# CP- VNR-3108LB-8P

## 8 Ch. 8PoE Network Video Recorder



### Feature

Processor  
Operating System  
IP Camera Input  
User Interface  
Video Output  
Compression  
Video Resolution  
Live Preview  
Video Recording  
Video Display Split  
Corridor Mode Screen  
Hard Disk  
Capability  
Playback  
Max User Account  
Interface Ports  
Ethernet  
Protocols  
PoE  
Power Supply  
Power Consumption  
Working Temp  
Working Humidity  
Dimensions  
Weight

### Specification

Dual-core embedded processor  
Embedded LINUX  
8 channel  
GUI  
HDMI, VGA  
Ultra 265/H.265/H.264  
HDMI: 1920x1080P@60Hz, 1920x1080P@50Hz, 1600x1200@60Hz, 1280x1024@60Hz, 1280x720@60Hz, 1024x768@60Hz, VGA: 1920x1080p@60Hz, 1920x1080p@50Hz, 1600x1200@60Hz, 1280x1024@60Hz, 1280x720@60Hz, 1024x768@60Hz  
1080p/960p/720p/D1/2CIF/CIF  
1080p/960p/720p/D1/2CIF/CIF  
1/4/8/9  
3/4/5/7/9  
1 SATA ports, up to 8TB  
4 x 1080p@20fps, 4 x 720p@30fps  
8 Ch. , 1080p/960p/720p/D1/2CIF/CIF  
128  
2 USB Port (2.0)  
1 RJ45 10M/100M self-adaptive Ethernet Interface  
P2P, UPnP, NTP, DHCP, PPPoE  
8 independent 100 Mbps PoE network interfaces (IEEE 802.3at, IEEE 802.3af)  
52V DC  
≤5.5 W (without HDD) , PoE: Max 30W for single port , Max 108W in total ( 13.5W for each)  
-10°C ~ + 55°C ( +14°F ~ +131°F )  
≤ 90% RH (non-condensing)  
205mm × 205mm × 42mm(8.1" × 8.1" × 1.7")  
0.7kg (without HDD)

