

CP- UNR-4K664R8-V2**64 Ch. H.265+ 4K Network Video Recorder****Main Features**

- Up to 64 channel IP camera input
- Up to 12Mp resolution preview and playback
- Max 384Mbps incoming bandwidth
- Support 8 SATA HDDs up to 8TB Each, 4 USB(2 USB3.0), 1 eSATA port
- 2 HDMI / 1 VGA simultaneous video output
- Support Multi-brand network cameras
- Support RAID 0/1/5/10
- ONVIF Version 2.4 conformance
- Support N + M Standby
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



CP- UNR-4K664R8-V2

64 Ch. H.265+ 4K Network Video Recorder



Feature

Processor
 IP Camera Input
 Operating System
 Two-way Talk
 User Interface
 Video Output
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Motion Detection
 Video Loss
 Camera Blank
 Alarm Input
 Alarm Output
 Hard Disk
 Smart Phone
 Trigger Events
 HDD Management
 Recording Mode
 Search Mode
 Playback
 Backup Mode
 Interface Ports
 Max User Account
 Record Interval
 Ethernet
 Protocols
 Power Supply
 Power Consumption
 Working Temp

Specification

Intel Quad-core Processor
 64 channel
 Embedded LINUX
 1 channel Input, 1 channel Output, RCA
 GUI
 2 HDMI (up to 3840× 2160), 1 VGA
 H.265+/H.265/H.264/MJPEG
 3840× 2160, 1920× 1080, 1280× 1024, 1280× 720, 1024× 768
 Max 384 Mbps
 The 1st screen: 1/4/8/9/16/25/36, The 2nd screen: 1/4/8/9/16
 MD Zones: 396(22×18).
 Supports
 Supports
 16ch, low level effective, green terminal interface
 8ch, NO/NC programmable, green terminal interface
 8 SATA III ports, up to 8TB Each, 1 eSATA port
 iPhone, iPad, Android
 Recording, PTZ, Tour, Alarm out, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips
 Single, Raid 0/1/5/10(Support global HDD hot-spare)
 Manual, Schedule (Regular, MD (Motion Detection) ,Alarm, IVS), Holiday, Stop
 Time /Date, Alarm, MD and Exact Search (accurate to second)
 128Mbps in Raid 5 mode, 64Mbps in single HDD mode
 USB Device/Network/eSATA Device
 2 HDMI, 1 VGA, Support Hot-swap, 4 USB ports(2 USB2.0, 2 USB3.0), 1 RS485, 1 RS232
 128 users
 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
 2 RJ-45 Ports (10/100M/1000Mbps)
 HTTP, HTTPs, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP,SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search , ONVIF 2.4, CGI Conformant
 AC100V~240V, 50~60Hz
 <20W(without HDD)
 -10°C ~ +55°C (+14°F ~ +131°F), 86 ~ 106kpa



 **CP- UNR-4K664R8-V2****64 Ch. H.265+ 4K Network Video Recorder****Feature**

Dimensions

Weight

Specification

444mm × 457.1mm × 95mm

9kg (without HDD)