

CP-SMR-41**4 Ch. AHD + 1 Ch. 720p H.264 Mobile DVR****Main Features**

- Supports 4 channels AHD +1 channels 720P
- Supports Hard disk for main recording
- Supports GPS for location tracking
- Vibration-resistant design to meet various environment needs.
- Supports USB2.0 high speed backup
- Pre-recording max. 60 mins
- Tamper-proof watermarks
- Modular design for easy maintenance



CP-SMR-41

4 Ch. AHD + 1 Ch. 720p H.264 Mobile DVR

Feature

Operating System

Control Mode

Operation Interface

Video Systems

Total Resource

Video Input

Video Output

Recording Mode

Audio Input

Pre-recording

Audio Output

Image Resolution

Display Split

Post-recording

Image Quality

OSD

GPS

Sensors

Search Mode

USB

Hard Disk

Ethernet

Video/Audio Compression

MIC

Serial Ports

Power Input

Power Output

Power Consumption

Dimension (WxHxD)

Weight

Specification

Linux 3.0.8

Easy Check

Semi-transparent GUI

Electrical level: 1Vpp Impedance : 75Ω NTSC/PAL Optional

PAL: (4x25)fps WD1+30fps 720P(IPC) Or (4x12)fps 720P(AHD)+30fps 720P(IPC) NTSC: (4x30)fps WD1 +30fps 720P (4x15)fps 720P(AHD)+30fps 720P(IPC)

4 channels WD1+1 channel 720P

1 channels

Boot up/Manual/Schedule/Alarm

5channels (1 channel IPC audio input)

0~60 minutes

1 channels

Analog: PAL: WD1, WHD1, WCIF, D1, HD1, CIF, NTSC, WD1, WHD1, WCIF, D1, HD1, CIF; Digital: 720P

1/4/9

0-30 minutes

1-8 levels adjustable (1 is the best)

GPS information, alarm, vehicle No., speed, date/time

Location tracking, speed detection and time sync

8 Inputs, 2 Outputs

Date/time, channel, event

USB 2.0 × 1

2.5" SATA HDD

6-pin DJ(100M x 1, PON power supply)

H.264/ADPCM

1 MIC interface

RS232 × 1

DC8-36V

5V@1A

32W

206mm × 190mm × 70.4mm

1.24Kg.

 **CP- SMR-41****4 Ch. AHD + 1 Ch. 720p H.264 Mobile DVR****Feature**

Operating Temperature

Relatively Operating Humidity

Certification

Specification

-40°C- +70°C(With heater) or -10°C- +70°C

8%~90%(no Condence)

CE, FCC