

CP-SMR-N411-PG**4 Ch. H.264 Mobile NVR****Main Features**

- 4 channels 1080P channel IPC
- Built-in 4G/3G for live view
- H.264 video compression
- Supports SD card for mirror recording
- Supports Hard disk for main recording
- Supports GPS for location tracking



CP-SMR-N411-PG

4 Ch. H.264 Mobile NVR

Feature

Operating System
Operation Interface
Control Mode
Video Compression
Video Systems
Total Resource
Resolution
Audio Compression
Video Input
Video Output
Recording Mode
Audio Input
Audio Output
Audio Signal Standard
Pre-recording
Display Split
Post-recording
Mirror/Dual Recording
OSD
Playback
Image Quality
GPS
Search Mode
Sensors
Backup Mode
USB
Hard Disk
MIC
Ethernet
4G/3G Support
Serial Ports
Control panel

Specification

Embedded Linux 3.0.8
Semi-transparent GUI
Network, mouse, Integrated Monitor
H.264
NTSC/PAL
4 x 1080P@30FPS (IPC)
Digital: 1080P(1920X1080), 720P(1280X720)
ADPCM
4 channels 1080P IPC
1 channel
Boot up/Manual/Schedule/Alarm
4 channels (4 channels IPC audio input)
1 channel
Electrical level: 2Vpp Input impedance: 4.7kΩ
0-60 minutes
1/4
0-30 minutes
Supports
GPS Location, Alarm, Vehicle No, Speed, Date/Time
1 channel by local playback
1-8 levels adjustable (1 is the best)
Location tracking, Speed detection and Time sync
Date/time, channel, event
8 Inputs, 2 Outputs
USB, HDD, Network
1 x USB2.0(Type A) + 1 x USB2.0(Type B)
Supports 2.5" SATA hard disk x 1
One MIC interface
Ethernet- RJ45 x 1 (10/100 M), IPC Ethernet- 4 x RJ45 (10/100 M POE port)
EVDO/WCDMA/TDD-LTE/FDD-LTE
RS232 x 2, RS485 x 2
Integrated Monitor

CP- SMR-N411-PG

4 Ch. H.264 Mobile NVR

Feature

Power Input

Interface Ports

Power Output

Power Consumption

Standby Power Consumption

Dimension (W×H×D)

Weight

Operating Temperature

Relatively Operating Humidity

Specification

DC8-36V, ACC

SD card slot x 1, 1 SIM slot, 1 channel pulse speed detection

5V@1A & 12V@1A

40W

≈0W

255.3mm x 150mm x 89.1mm

2.2 KG

-10°C ~ +70°C or -40°C ~ +70°C(with heater)

8%-90% (No Condense)