

**CP- UNC-TE21ZL10E-VMD****2 MP Full HD WDR Network IR Bullet Camera - 100 Mtr.****Main Features**

- 1/2.8" 2MP PS CMOS Image Sensor
- H.265 , H.264 triple-stream encoding
- Max. 50/60fps@1080P (1920×1080)
- WDR(120dB), Day/Night (ICR), 3D-DNR, ROI, AWB, AGC, BLC
- IR Range of 100 Mtrs.
- 7mm ~35mm motorized lens
- 2/1 Alarm in/out, 1/1 audio in/out
- Micro SD Card, IP67, IK10, ePoE
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro



# CP- UNC-TE21ZL10E-VMD

2 MP Full HD WDR Network IR Bullet Camera - 100 Mtr.



## Feature

Image Sensor  
 Effective Pixels  
 Minimum Illumination  
 Shutter Speed  
 White Balance  
 Lens  
 Gain Control (AGC)  
 Angle of View  
 Video Compression  
 Back Light Compensation  
 S/N Ratio  
 Video Streaming  
 Resolution  
 Video Output  
 Digital Zoom  
 Motion detection  
 Privacy Mask  
 ICR  
 ROI  
 Audio Input  
 Audio Output  
 Audio Compression  
 Alarm IN  
 Alarm Out  
 Bit Rate  
 Protocol  
 Smart Detection  
 Ethernet  
 User Account

## Specification

1/2.8" 2 Megapixel CMOS  
 1920(H) x 1080(V)  
 0.006Lux/F1.4 ( Color,1/3s,30IRE) 0.05Lux/F1.4 ( Color,1/30s,30IRE) 0Lux/F1.4 (IR on)  
 Auto/Manual, 1/3~1/100000s  
 Auto/Natural/Street Lamp/Outdoor/Manual  
 7mm~35mm Motorized Lens  
 Auto/Manual  
 H: 35°~12°, V:19°~7°  
 H.265+/H.265/H.264+/H.264  
 BLC / HLC / WDR(120dB)  
 More than 50 dB  
 Main Stream: 1080P(1~50/60fps) , Sub Stream: D1(1~50/60fps) , Third Stream: 1080P(1~25/30fps)  
 1080P(1920x1080)/1.3M(1280x960)/ 720P(1280x720)/D1(704x576/704x480)/ VGA(640x480)/CIF(352x288/352x240)  
 1 Port  
 16x  
 Off / On (4 Zone, Rectangle)  
 Off / On (4 Area, Rectangle)  
 Auto (ICR)/Color/B/W  
 Off / On (4 Zone)  
 1 Ch.  
 1 Ch.  
 G.711a/ G.711Mu/ AAC/ G.726  
 2 channel In: 5mA 5VDC  
 1 channel Out: 300mA 12VDC  
 H.264: 24~9472Kbps , H.265: 14~5632Kbps  
 HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP; NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP; ONVIF; PSIA; CGI  
 Tripwire, Intrusion, Object Abandoned/Missing, Face Detection  
 RJ-45 (10/100Base-T)  
 20 users



**CP- UNC-TE21ZL10E-VMD****2 MP Full HD WDR Network IR Bullet Camera - 100 Mtr.****Feature**

Smart Phone

IR

Micro SD

Operating Temperature

Humidity

Power Source

Power Consumption

Weatherproof Standard

Dimension

Weight

**Specification**

iPhone, iPad, Android Phone

IR Range of 100 Mtr.

Micro SD, Max 128GB

-30° C ~ +60° C (-22° F ~ +140° F)

Less than 95% RH

DC12V, ePoE

&lt;12.95W

IP67 &amp; IK10

273.2mm×95.0mm×95.0mm

1.11Kg