

CP- UNR-4K2041-P4V2**4 Ch. 4K 4PoE H.265 Network Video Recorder****Main Features**

- Support up to 1ch@8MP/4ch@1080P decoding
- Smart H.265+/Smart H.264+/H.265/H.264 decoding
- Up to 8MP resolution preview and playback
- Max 80Mbps incoming bandwidth
- Support 1 SATA HDDs up to 10TB, 2 USB ports(2.0), 4 PoE Ports
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



CP- UNR-4K2041-P4V2

4 Ch. 4K 4PoE H.265 Network Video Recorder

Feature

Processor
IP Camera Input
Operating System
Two-way Talk
User Interface
Video Output
Compression
Video Resolution
Video Recording
Video Display Split
Decoding Capacity
OSD
Motion Detection
Video Loss
Camera Blank
Smart Phone
Hard Disk
HDD Mode
Bit Rate
Trigger Events
Recording Mode
Search Mode
Sync Playback
Playback
Backup Mode
Interface Ports
Record Interval
Max User Access

Specification

Dual-core embedded processor
4 channel
Embedded LINUX
1 channel Input, 1 channel Output, RCA
GUI
1 HDMI, 1 VGA
Smart H.265+/H.265/Smart H.264+/H.264
HDMI: 3840×2160, 1920×1080, 1280×1024, 1280×720
VGA: 1920×1080, 1280×1024, 1280×720
Max 80 Mbps, 8MP/6MP/5MP/4MP/3MP/1080P/ 720P/ D1&etc.
1/4
1ch@8MP 30fps, 4ch@1080P 30fps
Camera title, Time, Camera lock, Motion detection, Recording
MD Zones: 396(22×18).
Supports
Supports
iPhone, iPad, Android Phone
1 SATA III ports, up to 10TB Each.
The maximum HDD capacity varies with environment temperature
Single
16Kbps ~ 20Mbps Per Channel
Recording, PTZ, Tour, Video Push, Snapshot, and Screen Tips
Manual, Schedule (Continuous, MD (Motion Detection), Alarm, IVS)
Time/Date, MD & Exact search (accurate to second)
1/4
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
USB Device / Network
2 USB Ports(1 Rear USB2.0, 1 Front USB2.0)
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
128 users

CP- UNR-4K2041-P4V2

4 Ch. 4K 4PoE H.265 Network Video Recorder

Feature

Ethernet

PoE Ports

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

1 RJ-45 port (10/100Mbps)

4 ports (IEEE802.3at/af)

HTTP/HTTPS, TCP/IP, IPv4/IPv6, RTSP, UDP, NTP, DHCP, DNS, IP Filter, DDNS, IP Search, InstaOn, ONVIF 2.4, SDK, CGI

Single, DC48V/1.25A

NVR: <3W (without HDD); PoE: Max 25.5w for single port, 50w in total

-10 ~+55°C / 10~90%RH / 86~106kpa

260 mm × 224.9 mm × 47.6 mm

0.8 kg (without HDD)