

**CP- UNR-725624****256 Channel Super Network Video Recorder****Main Features**

- Max 256ch IP cameras connection
- Max 512Mbps incoming bandwidth
- 2 HDMI (Different Source), 1 VGA, 8 HDMI (Optional)
- Support 24 hot-swap HDDs Up to 8 TB capacity for each HDD
- Supports RAID 0/1/5/6/10/50/60
- Support Multi-brand network cameras
- Supports iSCSI and Mini SAS for Expanded Storage Space
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



# CP- UNR-725624

## 256 Channel Super Network Video Recorder



### Feature

Main Processor  
Operating System  
Two-way Talk  
Compression  
Resolution  
User Interface  
Input  
Recording  
Playback  
Recording Resolution  
Recording Mode  
Protocol  
Search Mode  
Playback Function  
Backup Mode  
Interface  
Max. User Access  
Multi-screen Display  
Smart Phone  
Hard Disk  
Trigger Events  
HDD Mode  
Ethernet  
Motion Detection  
Video Detection  
Alarm Input  
Record Interval

### Specification

Intel® Core™ i7 Processors  
Embedded LINUX  
1 Channel Input, 1 Channel Output, RCA  
H.264/MJPEG  
1920 × 1080 , 1280 × 1024, 1280 × 720 , 1024 × 768  
GUI  
256 Channel  
512Mbps  
128 Mbps in Raid 5 Mode; 64 Mbps in single HDD Mode  
12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 1.3MP, 720P etc.  
Manual, Schedule (Regular, MD (Motion Detection), Alarm, IVS), Holiday, Stop  
HTTP, HTTPs, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search, ONVIF 2.4, CGI Conformant  
Time /Date, Alarm, MD and Exact Search (accurate to second)  
Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom  
USB Device/Network  
2 HDMI (Different Source), 1 VGA 8 HDMI (Optional), Support Hot-swap, 4 USB Ports (2 USB 2.0 , 2 USB 3.0), 1 RS485, 1 RS232  
128 users  
1st screen: 1/4/6/8/9/16/32/64, 2nd Screen: 1/4/8/9/16  
iPhone, iPad, Android  
24 SATA III Ports, up to 192TB, 1 eSATA Port  
Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips  
Single, Raid 0/1/5/6/10/50/60 (Support Global HDD Hot-spare), 2 Mini SAS Port, for Storage Expansion  
4 RJ-45 ports(10/100/1000M), 4 Ethernet ports joint working or 4 independent 1000Mbps Ethernet ports  
MD Zones: 396(22×18)  
Motion Detection, MD Zones: 396 (22 × 18), Video Loss and Tampering  
4ch, low level effective, green terminal interface  
1 ~ 120 min (default: 60 min), Pre-record: 1 ~ 30 sec, Post-record: 10 ~ 300 sec



**CP- UNR-725624****256 Channel Super Network Video Recorder****Feature**

Relay Output  
Front cover  
USB  
Power Supply  
Power Consumption  
Working Environment  
Dimension  
Weight

**Specification**

4 Channel, NO/NC Programmable, Green Terminal Interface  
Support Hot-swap  
4 USB Ports (2 USB 2.0 , 2 USB 3.0)  
AC100V ~ 240V, 50 ~ 60 Hz  
<200W (Without HDD)  
-10°C ~ +55°C, 0 ~ 90% RH, 86 ~ 106kpa  
482.6mm x 544.45mm x 175mm  
24.5kg (without HDD)