

CP- UVR-0401L1-4KH**4 Ch. 4K H.265 Cosmic HD DVR****Main Features**

- Auto Adaptive HDCVI/AHD/TVI/CVBS/IP signals
- Support upto 8MP IP Camera
- Max 24Mbps Incoming Bandwidth
- H.265+ /H.265 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 1 SATA HDD up to 10TB, 2 USB Ports(2.0)
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



CP- UVR-0401L1-4KH

4 Ch. 4K H.265 Cosmic HD DVR



Feature

Processor
 Operating System
 IP Camera Input
 Two-way Talk
 User Interface
 Video Input
 Video Output
 Video Standard
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 OSD
 Audio Input
 Audio Output
 Motion Detection
 Video Loss
 Camera Blank
 Audio Compression
 Hard Disk
 Audio Sample Rate
 Smart Phone
 Audio Bit Rate
 Trigger Events
 Recording Mode
 Search Mode
 Playback

Specification

Embedded processor
 Embedded LINUX
 4+2 Ch. : each channel up to 8MP
 Reuse audio in/out, RCA
 GUI
 4 channel, BNC
 1 HDMI, 1 VGA
 Analog: NTSC(525Line, 60f/s), PAL(625Line, 50f/s)
 H.265+/H.265/H.264+/H.264
 HDMI: 2560×1440, 1920×1080, 1280×1024, 1280×720, VGA: 1920×1080, 1280×1024, 1280×720
 Main stream:1st Ch. 4K(1~7fps),6MP(1~10fps),5MP(1~12fps),4MP/3MP(1~15fps),others 4K-N (1~7fps),4MP/3MP(1~15fps);4M-N/1080P/720P/960H/D1/CIF (1~25/30fps),Sub stream: 960H(1~15fps); D1/CIF(1~25/30fps)
 1/4
 Camera title, Time, Video loss, Camera lock, Motion detection, Recording
 1 channel, RCA
 1 channel, RCA
 MD Zones: 396 (22 × 18)
 Supports
 Supports
 AAC (only for the 1st channel), G.711A, G.711U, PCM
 1 SATA port, up to 10TB
 8KHz, 16 bit Per Channel
 iPhone, iPad, Android Phone
 64Kbps Per Channel
 Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
 Manual, Schedule (General, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop
 Time /Date, Alarm, MD and Exact Search (accurate to second)
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom



CP- UVR-0401L1-4KH

4 Ch. 4K H.265 Cosmic HD DVR



Feature

Backup Mode
Interface Ports
Max User Account
Record Interval
Ethernet
Protocols
Power Supply
Power Consumption
Working Temp
Dimensions
Weight

Specification

USB Device/ Network
1 HDMI, 1 VGA, 2 USB Ports(2.0), 1 RS485
128 users
1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
1 RJ-45 port (100M)
HTTP, HTTPS, TCP/IP, IPv4/IPv6, Wi-Fi, 3G/4G, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, IP Search, ONVIF 16.12, CGI Conformant
DC12V/2A
<10W(without HDD)
-10 ~+55°C / 10~90%RH
260mm x 236mm x 48mm
0.9kg (without HDD)

