

CP- UVR-0808K1-H**8 Ch. 1080P H.265 Cosmic HD DVR****Main Features**

- Auto Adaptive HDCVI/AHD/TVI/CVBS/IP signals
- Support upto 6MP IP Camera
- Max 48Mbps Incoming Bandwidth
- H.265+ / H.265 dual-stream video compression
- HDMI / VGA Simultaneous Video Output
- Support 1 SATA HDD up to 10TB, 2 USB Ports(2.0)
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



CP- UVR-0808K1-H

8 Ch. 1080P H.265 Cosmic HD DVR



Feature

Processor
 IP Camera Input
 Operating System
 Two-way Talk
 User Interface
 Video Input
 Video Output
 Video Standard
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Bit Rate
 Audio Input
 Audio Output
 Motion Detection
 Video Loss
 Audio Compression
 Camera Blank
 Alarm Input
 Alarm Output
 Smart Phone
 Audio Sample Rate
 Hard Disk
 Audio Bit Rate
 Trigger Events
 Recording Mode
 Search Mode
 Playback

Specification

Embedded processor
 8+4 Ch. : each channel up to 6MP
 Embedded LINUX
 Reuse audio in (channel 1)/out, RCA
 GUI
 8 channel, BNC
 1 HDMI, 1 VGA
 Analog: NTSC(525Line, 60f/s), PAL(625Line, 50f/s)
 H.265+/H.265/H.264+/H.264
 1920 × 1080, 1280 × 1024, 1280 × 720, 1024 × 768
 Main stream: 4M-N/1080P(1~15fps); 1080N/720P/960H/ D1/CIF (1~25/30fps), Sub stream: D1/CIF(1~15fps)
 1/4/8/9
 32Kbps ~ 6144Kbps Per Channel
 8 channel
 1 channel
 MD Zones: 396 (22 × 18)
 Supports
 AAC (only for the 1st channel), G.711A, G.711U, PCM
 Supports
 8 channel
 3 channel
 iPhone, iPad, Android, Phone
 8KHz, 16 bit Per Channel
 1 SATA port, up to 10TB
 64Kbps Per Channel
 Recording, PTZ, Tour, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
 Manual, Schedule (General, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop
 Time /Date, Alarm, MD and Exact Search (accurate to second)
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom



CP- UVR-0808K1-H**8 Ch. 1080P H.265 Cosmic HD DVR****Feature**

Backup Mode

Interface Ports

Max User Account

Record Interval

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

USB Device/Network

1 HDMI, 1 VGA, 2 USB Ports(2.0), 1 RS485

128 users

1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

RJ-45 port (100M)

HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, IP Search, ONVIF 16.12, CGI Conformant

DC12V/2A

<10W(without HDD)

-10 ~+55°C / 10~90%RH

325mm x 255mm x 55mm

1.2KG (without HDD)