

CP-UVR-1601E1-H**16 Ch. 1080P Lite Cosmic HD DVR****Main Features**

- Auto Adaptive HDCVI/AHD/TVI/CVBS/IP signals
- Support upto 6 MP IP Camera
- Max 72Mbps Incoming Bandwidth
- H.265 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 1 SATA HDD up to 10TB, 2 USB Ports(2.0)
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



CP- UVR-1601E1-H

16 Ch. 1080P Lite Cosmic HD DVR



Feature

Processor
 IP Camera Input
 Operating System
 Two-way Talk
 User Interface
 Video Input
 Video Output
 Video Standard
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Audio Input
 Audio Output
 Motion Detection
 Video Loss
 Camera Blank
 Audio Compression
 Hard Disk
 Audio Sample Rate
 Smart Phone
 Audio Bit Rate
 Trigger Events
 Recording Mode
 Search Mode
 Playback
 Backup Mode
 Interface Ports

Specification

Embedded processor
 16+2:each channel up to 6MP
 Embedded LINUX
 Reuse audio in/out, RCA
 GUI
 16 channel, BNC
 1 HDMI, 1 VGA
 Analog: NTSC(525Line, 60f/s), PAL(625Line, 50f/s)
 H.265/H.264
 1920×1080, 1280×1024, 1280×720
 Main Stream:1st channel 1080N/720P(1~25/30fps), others 1080N/720P(1~15fps); 960H/D1/
 CIF (1~25/30fps), Sub stream: CIF (1~7fps)
 1/4/8/9/16
 1 channel, RCA
 1 channel, RCA
 MD Zones: 396 (22 × 18)
 Supports
 Supports
 AAC (only for the 1st channel), G.711A, G.711U, PCM
 1 SATA port, up to 10TB
 8KHz, 16 bit Per Channel
 iPhone, iPad, Android Phone
 64Kbps Per Channel
 Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
 Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video
 Loss, Tampering), Alarm, Stop
 Time /Date, Alarm, MD and Exact Search (accurate to second)
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous
 camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom
 USB Device/ Network
 1 HDMI, 1 VGA, 2 USB2.0, 1 RS485



CP- UVR-1601E1-H

16 Ch. 1080P Lite Cosmic HD DVR



Feature

Max User Account

Record Interval

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

128 users

1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

1 RJ-45 port (100M)

HTTP, HTTPS, TCP/IP, IPv4/IPv6, Wi-Fi, 3G/4G, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, IP Search, ONVIF 16.12, CGI Conformant

DC12V/2A

<10W(without HDD)

-10 ~+55°C / 10~90%RH

260mm×236mm×48mm

1.0kg(without HDD)