

CP-UVR-1601E2-H**16 Ch. 1080P Lite H.265 Cosmic HD DVR****Main Features**

- Auto Adaptive HDCVI/AHD/TVI/CVBS/IP signals
- Support upto 6MP IP Camera
- Max 72Mbps Incoming Bandwidth
- H.265 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 2 SATA HDD up to 10TB Each, 2 USB Ports(2.0)
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



CP- UVR-1601E2-H

16 Ch. 1080P Lite H.265 Cosmic HD DVR



Feature

Processor
IP Camera Input
Operating System
Two-way Talk
User Interface
Video Input
Video Output
Video Standard
Compression
Video Resolution
Video Recording
Video Display Split
Audio Input
Audio Output
Motion Detection
Video Loss
Camera Blank
Audio Compression
Hard Disk
Audio Sample Rate
Smart Phone
Audio Bit Rate
Trigger Events
Recording Mode
Search Mode
Playback
Backup Mode
Interface Ports

Specification

Embedded processor
16+2: each channel up to 6MP
Embedded LINUX
Reuse audio in/out, RCA
GUI
16 channel, BNC
1 HDMI, 1 VGA
Analog: NTSC(525Line, 60f/s), PAL(625Line, 50f/s)
H.265/H.264
1920×1080, 1280×1024, 1280×720
Main Stream: the 1st channel 1080N/720P(1~25/30fps), others 1080N/720P(1~15fps); 960H/D1/CIF (1~25/30fps), Sub stream: CIF (1~7fps)
1/4/8/9/16
1 channel, RCA
1 channel, RCA
MD Zones: 396 (22 × 18)
Supports
Supports
AAC (only for the 1st channel), G.711A, G.711U, PCM
2 SATA port, up to 10TB Each
8KHz, 16 bit Per Channel
iPhone, iPad, Android Phone
64Kbps Per Channel
Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
Manual, Schedule ((General, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop
Time /Date, Alarm, MD and Exact Search (accurate to second)
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom
USB Device/ Network
1 HDMI, 1 VGA, 2 USB2.0, 1 RS485



CP-UVR-1601E2-H**16 Ch. 1080P Lite H.265 Cosmic HD DVR****Feature**

Max User Account

Record Interval

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

128 users

1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

1 RJ-45 port (100M)

HTTP, HTTPS, TCP/IP, IPv4/IPv6, Wi-Fi, 3G/4G, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, IP Search, ONVIF 16.12, CGI Conformant

DC12V/4A

<10W(without HDD)

-10 ~+55°C / 10~90%RH

375mm×287mm×53mm

1.6kg(without HDD)